

Foreman - Bug #1001

Foreman insists on being able to detect a PXE boot server

06/22/2011 08:10 AM - Anonymous

Status: Closed	
Priority: Normal	
Assignee: Ohad Levy	
Category: DHCP	
Target version: 0.4	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description	
<p>When configuring foreman explicitly without PXE, adding a host is not possible because the bootserver method in app/models/orchestration/dhcp.rb fails to detect a default bootserver. The error in the Web UI is:</p> <pre>"# failed to detect boot server: undefined method `bootServer' for nil:NilClass"</pre> <p>Changing the bootserver method to:</p> <pre>def bootserver return "127.0.0.1"</pre> <p>made the error go away. Thanks to Ohad for the debugging.</p>	

Associated revisions

Revision b79bd65c - 07/11/2011 03:51 AM - Ohad Levy

fixes #1001, foreman should not use dhcp next server when tftp is not used

History

#1 - 07/11/2011 03:50 AM - Ohad Levy

- Category set to DHCP
- Assignee set to Ohad Levy
- Target version set to 0.4

#2 - 07/11/2011 03:52 AM - Ohad Levy

- Status changed from New to Closed
- % Done changed from 0 to 100

Applied in changeset [b79bd65cce0f2f47d730376d9eea99a23666b2c0](#).