

## Foreman - Refactor #10413

### Reimplement !unattended mode support as mainline feature

05/07/2015 09:57 AM - Dominic Cleal

<b>Status:</b>	Closed	
<b>Priority:</b>	Normal	
<b>Assignee:</b>	Tomer Brisker	
<b>Category:</b>	Host creation	
<b>Target version:</b>		
<b>Difficulty:</b>		<b>Fixed in Releases:</b> 3.3.0
<b>Triaged:</b>	No	<b>Found in Releases:</b>
<b>Bugzilla link:</b>		<b>Red Hat JIRA:</b>
<b>Pull request:</b>	<a href="https://github.com/theforeman/foreman/pull/8980">https://github.com/theforeman/foreman/pull/8980</a> , <a href="https://github.com/theforeman/foreman/pull/8983">https://github.com/theforeman/foreman/pull/8983</a>	

#### Description

settings.yaml contains :unattended set to true by default, which enables provisioning related features during initialisation. Turning it off is meant to put Foreman into a reporting-only mode, suitable for use as a dashboard, but it's notoriously unreliable and untested.

Many major releases contain regressions because !unattended users are a minority and all developers and tests run with unattended enabled in order to test all features.

I'd suggest that we should remove this global setting and make sure Foreman can operate sensibly and be well-tested with both reporting-only and provisioning usage in a single, default configuration.

The main difference was always the New Host page, which had significant behaviour differences around OS requirements and the tabs shown. When in unattended mode, it is only possible to create a managed host in the New Host form.

Related is that there's an inconsistency in use of the host "managed" flag. Generally when unattended is enabled and hosts are !managed, Foreman acts similarly to !unattended mode. We should probably migrate hosts created under !unattended to being !managed hosts and then have Foreman work well with both managed and !managed hosts.

Related again, consider how Host::Managed should be split up or renamed when it's an unmanaged host.

#### Related issues:

Related to Foreman - Bug #10307: Editing a host with "unattended: false" set ...	<b>Closed</b>	<b>04/29/2015</b>
Related to Foreman - Bug #10379: Facts import error: no superclass method `se...	<b>Closed</b>	<b>05/05/2015</b>
Related to Foreman - Bug #4018: API host creation fails with 500 error when u...	<b>New</b>	<b>01/15/2014</b>
Related to Foreman - Bug #16866: Facts import doesn't work with unattended=false	<b>Closed</b>	<b>10/11/2016</b>

#### Associated revisions

##### Revision 2481080e - 12/09/2021 09:51 AM - Tomer Brisker

Refs #10413 - Deprecate setting unattended: false

This setting is rarely used and complicates the code quite a lot. With the introduction of host registration, there is a path for any remaining users who had been using Foreman only for inventory to add their hosts.

##### Revision e8eeacf5 - 03/09/2022 09:05 PM - Tomer Brisker

Refs #10413 - Force :unattended: true

##### Revision 11febf2d - 03/09/2022 09:05 PM - Tomer Brisker

Refs #10413 - Remove unattended: false from tests

##### Revision f732d6ed - 03/09/2022 09:05 PM - Tomer Brisker

Refs #10413 - Remove unattended mode check in routes

**Revision 0350ff55 - 03/09/2022 09:05 PM - Tomer Brisker**

Refs #10413 - Drop unattended mode check in app init

**Revision c67703aa - 03/09/2022 09:05 PM - Tomer Brisker**

Refs #10413 - Drop unattended mode checks from models

**Revision 534f3f80 - 03/09/2022 09:05 PM - Tomer Brisker**

Refs #10413 - Drop unattended mode checks in helpers

**Revision 96039c6a - 03/09/2022 09:05 PM - Tomer Brisker**

Refs #10413 - Drop unattended mode checks from menu

**Revision c45d2f1b - 03/09/2022 09:05 PM - Tomer Brisker**

Refs #10413 - Drop unattended mode check in controllers

**Revision 1548de49 - 03/09/2022 09:05 PM - Tomer Brisker**

Refs #10413 - Drop unattended mode checks from views

**Revision e231a35e - 03/09/2022 09:05 PM - Tomer Brisker**

Fixes #10413 - Drop unattended mode deprecation

## History

---

**#1 - 05/07/2015 09:58 AM - Dominic Cleal**

- Related to Bug #10307: Editing a host with "unattended: false" set in settings.yaml results in error. added

**#2 - 05/07/2015 10:37 AM - Marek Hulán**

- Related to Bug #10379: Facts import error: no superclass method `setup\_clone' for #<Host::Managed...> added

**#3 - 05/07/2015 04:23 PM - Rickard von Essen**

- Related to Bug #4018: API host creation fails with 500 error when unattended == false added

**#4 - 10/11/2016 12:34 PM - Anonymous**

- Related to Bug #16866: Facts import doesn't work with unattended=false added

**#5 - 12/08/2021 05:08 PM - The Foreman Bot**

- Status changed from New to Ready For Testing

- Assignee set to Tomer Brisker

- Pull request <https://github.com/foreman/foreman/pull/8980> added

**#6 - 12/09/2021 09:56 AM - Ondřej Ezr**

- Fixed in Releases 3.0.2, 3.1.0 added

**#7 - 12/09/2021 10:01 AM - Ondřej Ezr**

- Fixed in Releases deleted (3.0.2, 3.1.0)

**#8 - 12/09/2021 12:47 PM - The Foreman Bot**

- Pull request <https://github.com/foreman/foreman/pull/8983> added

**#9 - 03/09/2022 09:05 PM - The Foreman Bot**

- Fixed in Releases 3.3.0 added

**#10 - 03/09/2022 10:00 PM - Tomer Brisker**

- Status changed from Ready For Testing to Closed

Applied in changeset [foreman|e231a35e05dc4b958c3244d674deeb21654b11d8](#).