

Foreman - Bug #1060

Problem with puppet-master variable

07/21/2011 09:08 AM - NoName NoSurname

Status:	Duplicate	Fixed in Releases: Found in Releases: Red Hat JIRA:
Priority:	Normal	
Assignee:		
Category:		
Target version:		
Difficulty:		
Triaged:		
Bugzilla link:		
Pull request:		
Description		
In the default Kickstart there's a reference to the puppet.conf snippet stored in foreman.		
In the snippet puppet.conf we've "server = <%= @host.puppetmaster %>" which, I assume is set by the settings -> proxy -> proxy value ?		
At the end, on the new installed client I find "server = puppet" instead of the "real" server value I set in hostgroups (puppet-master).		
Thanks		
Related issues:		
Is duplicate of Foreman - Bug #1745: If FQDN for puppetmaster starts with "pu...		Closed
		07/11/2012

History

- #1 - 04/20/2012 01:49 PM - Dale Dude
- I have the same issue with foreman-0.4.2-0.1.noarch. When using a "Puppet Master Proxy" for a host the "Puppet Master FQDN" is always stripped of the main domain. i.e. "puppet.mydomain.com" is my puppet master but no matter what I put in "Puppet Master FQDN" it ends up being just "puppet" without the "mydomain.com".
- #2 - 06/18/2013 09:10 AM - Benjamin Papillon
- Status changed from New to Duplicate