

Foreman - Bug #1060

Problem with puppet-master variable

07/21/2011 09:08 AM - NoName NoSurname

Status: Duplicate	
Priority: Normal	
Assignee:	
Category:	
Target version:	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description In the default Kickstart there's a reference to the puppet.conf snippet stored in foreman. In the snippet puppet.conf we've "server = <%= @host.puppetmaster %>" which, I assume is set by the settings -> proxy -> proxy value ? At the end, on the new installed client I find "server = puppet" instead of the "real" server value I set in hostgroups (puppet-master). Thanks	
Related issues: Is duplicate of Foreman - Bug #1745: If FQDN for puppetmaster starts with "pu... Closed 07/11/2012	

History

#1 - 04/20/2012 01:49 PM - Dale Dude

I have the same issue with foreman-0.4.2-0.1.noarch. When using a "Puppet Master Proxy" for a host the "Puppet Master FQDN" is always stripped of the main domain. i.e. "puppet.mydomain.com" is my puppet master but no matter what I put in "Puppet Master FQDN" it ends up being just "puppet" without the "mydomain.com".

#2 - 06/18/2013 09:10 AM - Benjamin Papillon

- Status changed from New to Duplicate