

Foreman - Bug #11050

Host Groups do not allow to specify image-based builds

07/08/2015 10:38 AM - Igor Galic

Status: New	
Priority: Normal	
Assignee:	
Category: Host creation	
Target version:	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description When creating host-groups it is not possible to mark the host-group as image-based. This is either a misshapen way to prevent us from creating Host-Groups which cannot be used for bare-metal deployments, or an simply a slip, since it's well possible to create Host-Groups with a specific Compute-Profiles, which don't make sense for bare-metal deployments either	
Related issues:	
Related to Foreman - Bug #10237: Host.new and API disregard provision_method	Duplicate 04/22/2015
Related to Foreman - Feature #5790: Default "Deploy on" value for host groups.	Closed
Has duplicate Foreman - Feature #14278: Provisioning method in host group	Duplicate 03/18/2016

History

#1 - 07/08/2015 10:41 AM - Dominic Cleal

- Related to Bug #10237: Host.new and API disregard provision_method added

#2 - 07/08/2015 10:42 AM - Dominic Cleal

- Category set to Host creation

I agree this ought to be an option, though I'm a little undecided whether it should be on the host group or the compute profile.

Linking to [#10237](#) as although it's a different problem, it's linked in that profiles can contain the image attribute which may guide the CR behaviour irrespective of the provision_method on the host. Both might have to be fixed to make it work well.

#3 - 07/09/2015 07:51 AM - Dominic Cleal

- Related to Feature #5790: Default "Deploy on" value for host groups. added

#4 - 03/21/2016 04:09 AM - Dominic Cleal

- Has duplicate Feature #14278: Provisioning method in host group added