

Foreman - Bug #11473

Not able to set domain in interfaces initially

08/24/2015 05:11 PM - Ryan Dyer

<b>Status:</b>	Closed	<b>Fixed in Releases:</b>  <b>Found in Releases:</b> 1.9.0  <b>Red Hat JIRA:</b>
<b>Priority:</b>	Normal	
<b>Assignee:</b>	Dominic Cleal	
<b>Category:</b>	Host creation	
<b>Target version:</b>	1.9.1	
<b>Difficulty:</b>		
<b>Triaged:</b>		
<b>Bugzilla link:</b>		
<b>Pull request:</b>	<a href="https://github.com/theforeman/foreman/pull/2682">https://github.com/theforeman/foreman/pull/2682</a>	
<b>Description</b>		
<p>I am seeing a behavior with 1.9.0 that I believe is a bug.</p> <p>Setup:</p> <p>Two puppet environments defined. (dev and factory)</p> <p>Single domain defined. (domain.com)</p> <p>Multiple subnets defined all belonging to the domain above.</p> <p>Create a new host, select one of the puppet environments. Go to Interfaces and select edit. Attempt to set the Domain. There is no drop down. Cancel the edit interfaces dialog screen. Re-Edit and the drop down for the domain will work just fine. Also if you do not select a puppet environment initially, you can go to the edit dialog and select a domain. The issue seems to be related to selecting a puppet environment and then attempting to edit the interface. A quick cancel and re-edit resolves the issue.</p> <p>I have tried this under chrome and IE with the same results</p>		
<b>Related issues:</b>		
Related to Foreman - Feature #10641: Ability to search VmWare networks		<b>Closed</b> <b>05/28/2015</b>

Associated revisions

Revision 501853b5 - 09/10/2015 08:01 AM - Dominic Cleal

fixes #11473 - remove re-init of domain select2 on env selection

After an environment was selected, the reloadOnAjaxComplete function re-initialised every select2, but other dropdowns triggered onContentLoaded which excluded those with the without\_select class.

Change reloadOnAjaxComplete to be consistent and also explicitly re-init the subnet dropdown when the domain dropdown causes it to change.

Also destroy select2 fields before storing the interface in the "hidden" storage, allowing it to be re-initialised when the modal is displayed again.

Revision aaf7d7a0 - 09/11/2015 07:38 AM - Dominic Cleal

fixes #11473 - remove re-init of domain select2 on env selection

After an environment was selected, the reloadOnAjaxComplete function re-initialised every select2, but other dropdowns triggered onContentLoaded which excluded those with the without\_select class.

Change reloadOnAjaxComplete to be consistent and also explicitly re-init the subnet dropdown when the domain dropdown causes it to change.

Also destroy select2 fields before storing the interface in the "hidden" storage, allowing it to be re-initialised when the modal is displayed again.

## History

---

### #1 - 08/26/2015 08:00 AM - Dominic Cleal

- *Related to Feature #10641: Ability to search VmWare networks added*

### #2 - 08/26/2015 08:00 AM - Dominic Cleal

- *translation missing: en.field\_release set to 72*

### #3 - 09/04/2015 09:56 AM - Marek Hulán

I reproduced the issue, it seems related to select2, web console prints following

```
Uncaught TypeError: Cannot read property 'hasClass' of null
```

when I click on domain select box. It fails after selection of any environment even if domain is already set, you go back to first tab, select an environment and get back to interfaces form. It seems that only environment selection breaks the select2 js, if you change deploy on or other field that also redraw the form, domain selection works again.

### #4 - 09/07/2015 11:14 AM - Dominic Cleal

- *Status changed from New to Assigned*

- *Assignee set to Dominic Cleal*

### #5 - 09/08/2015 03:39 AM - The Foreman Bot

- *Status changed from Assigned to Ready For Testing*

- *Pull request <https://github.com/theforeman/foreman/pull/2682> added*

- *Pull request deleted ()*

### #6 - 09/10/2015 09:02 AM - Dominic Cleal

- *Status changed from Ready For Testing to Closed*

- *% Done changed from 0 to 100*

Applied in changeset [501853b511d52f078c1d0933afec955b25356e54](#).