

Foreman - Bug #1175

PXELinux does not render with spoof

09/20/2011 10:12 AM - Jacob McCann

Status: Closed	
Priority: Normal	
Assignee: Jacob McCann	
Category: Unattended installations	
Target version: 1.0	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description	
URL ">https://&lt;hostname&gt;/unattended/PXELinux?spoof=&lt;ip>	
Returns:	
<pre>Processing UnattendedController#PXELinux (for <ip workstation> at 2011-09-20 07:49:03) [GET] Parameters: {"spoof"=>"<ip>"} undefined method `configTemplate' for nil:NilClass /srv/www/usps-puppet-foreman/app/controllers/unattended_controller.rb:143:in `unattended_local' /srv/www/usps-puppet-foreman/app/controllers/unattended_controller.rb:70:in `PXELinux' Rendering common/500 (500)</pre>	

Associated revisions

Revision 77440fe6 - 01/29/2012 09:11 AM - Ohad Levy

fixes #1175 - PXELinux does not render with spoof

History

#1 - 01/29/2012 07:50 AM - Ohad Levy

- Category set to *Unattended installations*
- Target version set to *1.0*

#2 - 01/29/2012 09:58 AM - Ohad Levy

- Status changed from *New* to *Closed*
- % Done changed from *0* to *100*

Applied in changeset [77440fe634d02710c596cb77ca05d1705d68fbe3](https://bugzilla.redhat.com/show_bug.cgi?id=1175).