

Foreman - Bug #12343

puppet class overrides not working as expected

10/28/2015 06:51 PM - Michael Eklund

<b>Status:</b>	Closed	
<b>Priority:</b>	Normal	
<b>Assignee:</b>	Ori Rabin	
<b>Category:</b>	Puppet integration	
<b>Target version:</b>	1.10.0	
<b>Difficulty:</b>		<b>Fixed in Releases:</b>
<b>Triaged:</b>		<b>Found in Releases:</b> 1.10.0
<b>Bugzilla link:</b>		<b>Red Hat JIRA:</b>
<b>Pull request:</b>	https://github.com/foreman/foreman/pull/2878	
<b>Description</b> <a href="https://cfg01.atl.dealnews.net/hosts/cfg01.atl.dealnews.net/externalNodes?name=cfg01.atl.dealnews.net">https://cfg01.atl.dealnews.net/hosts/cfg01.atl.dealnews.net/externalNodes?name=cfg01.atl.dealnews.net</a> allowed overrides on puppetdb set them on the host ( <a href="https://www.evernote.com//APfgCjSqAd5J4pv7cvRW43lSl652HfQGbSl">https://www.evernote.com//APfgCjSqAd5J4pv7cvRW43lSl652HfQGbSl</a> ) matchers showed up in class ( <a href="https://www.evernote.com//APet0mTtLE9C55lkWH09nMC39lkO5JINcfY">https://www.evernote.com//APet0mTtLE9C55lkWH09nMC39lkO5JINcfY</a> , <a href="https://www.evernote.com//APdmwVx34tFILokNE1pePio_BNzFQgmkgI">https://www.evernote.com//APdmwVx34tFILokNE1pePio_BNzFQgmkgI</a> )  but not in only one in yaml:  --- classes: profile::base: puppetdb: puppetdb::master::config: puppet_service_name: puppetserver strict_validation: true parameters: puppetmaster: cfg01.atl.dealnews.net		

Associated revisions

Revision 28a5d0bb - 10/29/2015 12:26 PM - Ori Rabin

Fixes #12343 - Fixing parameters caster for boolean values

Revision d56f562b - 11/16/2015 09:30 AM - Ori Rabin

Fixes #12343 - Fixing parameters caster for boolean values

(cherry picked from commit 28a5d0bb293d1ab2e8f171910b19f1deed2d79cb)

History

- #1 - 10/29/2015 04:19 AM - Dominic Cleal
- Description updated
  - Category set to Puppet integration

Could you run these debugging lines from foreman-rake console please? It may help narrow the bug down.

```
c = Classification::ClassParam.new(:host => Host.find('cfg01.atl.dealnews.net'))
c.send(:values_hash)
LookupValue.where(:match => 'fqdn=cfg01.atl.dealnews.net')
```

- #2 - 10/29/2015 08:01 AM - Tomer Brisker
- Status changed from New to Assigned
  - Assignee set to Ori Rabin

### #3 - 10/29/2015 08:35 AM - Tomer Brisker

This is caused by <https://github.com/theforeman/foreman/blob/develop/app/services/foreman/parameters/caster.rb#L13>:

```
@value = @options[:value] || @item.send(@options[:attribute_name])
```

which sets the wrong value if @options[:value] is false.

### #4 - 10/29/2015 09:10 AM - The Foreman Bot

- Status changed from Assigned to Ready For Testing
- Pull request <https://github.com/theforeman/foreman/pull/2878> added
- Pull request deleted ()

### #5 - 10/29/2015 10:09 AM - Michael Eklund

```
root@cfg01:~# foreman-rake console
For some operations a user must be set, try User.current = User.first
Loading production environment (Rails 3.2.21)
irb(main):001:0> c = Classification::ClassParam.new(:host => Host.find('cfg01.atl.dealnews.net'))
Host::Managed Load (1.8ms)  SELECT "hosts".* FROM "hosts" WHERE "hosts"."type" IN ('Host::Managed') AND "hos
ts"."name" = 'cfg01.atl.dealnews.net' LIMIT 1
=> #<Classification::ClassParam:0x000000077765f8 @host=#<Host::Managed id: 1, name: "cfg01.atl.dealnews.net",
last_compile: "2015-10-28 22:23:56", last_report: "2015-10-28 22:23:52", updated_at: "2015-10-28 22:24:22", cr
eated_at: "2015-10-28 17:23:08", root_pass: "", architecture_id: 1, operatingsystem_id: 1, environment_id: 1,
ptable_id: nil, medium_id: nil, build: false, comment: "", disk: "", installed_at: nil, model_id: 1, hostgroup
_id: 2, owner_id: 3, owner_type: "User", enabled: true, puppet_ca_proxy_id: 1, managed: true, use_image: nil,
image_file: nil, uuid: nil, compute_resource_id: nil, puppet_proxy_id: 1, certname: "cfg01.atl.dealnews.net",
image_id: nil, organization_id: nil, location_id: nil, type: "Host::Managed", otp: nil, realm_id: nil, compute
_profile_id: nil, provision_method: nil, grub_pass: "", global_status: 0, lookup_value_matcher: "fqdn=cfg01.at
l.dealnews.net">, @safe_render=#<SafeRender:0x00000007a1b6c8 @allowed_methods=[], @allowed_vars={:host=>#<Host
::Managed id: 1, name: "cfg01.atl.dealnews.net", last_compile: "2015-10-28 22:23:56", last_report: "2015-10-28
22:23:52", updated_at: "2015-10-28 22:24:22", created_at: "2015-10-28 17:23:08", root_pass: "", architecture_
id: 1, operatingsystem_id: 1, environment_id: 1, ptable_id: nil, medium_id: nil, build: false, comment: "", di
sk: "", installed_at: nil, model_id: 1, hostgroup_id: 2, owner_id: 3, owner_type: "User", enabled: true, puppe
t_ca_proxy_id: 1, managed: true, use_image: nil, image_file: nil, uuid: nil, compute_resource_id: nil, puppet_
proxy_id: 1, certname: "cfg01.atl.dealnews.net", image_id: nil, organization_id: nil, location_id: nil, type:
"Host::Managed", otp: nil, realm_id: nil, compute_profile_id: nil, provision_method: nil, grub_pass: "", globa
l_status: 0, lookup_value_matcher: "fqdn=cfg01.atl.dealnews.net">>>
irb(main):002:0> c.send(:values_hash)
Environment Load (0.7ms)  SELECT "environments".* FROM "environments" WHERE "environments"."id" = 1 ORDER BY
environments.name LIMIT 1
Hostgroup Load (1.0ms)  SELECT "hostgroups".* FROM "hostgroups" WHERE "hostgroups"."id" = 2 ORDER BY hostgro
ups.title LIMIT 1
Hostgroup Load (0.9ms)  SELECT "hostgroups".* FROM "hostgroups" WHERE "hostgroups"."id" IN (3, 1, 2) ORDER B
Y (case when hostgroups.ancestry is null then 0 else 1 end), hostgroups.ancestry
SQL (0.8ms)  SELECT "config_groups".id FROM "config_groups" INNER JOIN "host_config_groups" ON "config_group
s"."id" = "host_config_groups"."config_group_id" WHERE "host_config_groups"."host_id" = 3 AND "host_config_gro
ups"."host_type" = 'Hostgroup' ORDER BY config_groups.name
SQL (0.5ms)  SELECT "config_groups".id FROM "config_groups" INNER JOIN "host_config_groups" ON "config_group
s"."id" = "host_config_groups"."config_group_id" WHERE "host_config_groups"."host_id" = 1 AND "host_config_gro
ups"."host_type" = 'Hostgroup' ORDER BY config_groups.name
SQL (0.5ms)  SELECT "config_groups".id FROM "config_groups" INNER JOIN "host_config_groups" ON "config_group
s"."id" = "host_config_groups"."config_group_id" WHERE "host_config_groups"."host_id" = 2 AND "host_config_gro
ups"."host_type" = 'Hostgroup' ORDER BY config_groups.name
SQL (0.6ms)  SELECT "config_groups".id FROM "config_groups" INNER JOIN "host_config_groups" ON "config_group
s"."id" = "host_config_groups"."config_group_id" WHERE "host_config_groups"."host_id" = 1 AND "host_config_gro
ups"."host_type" = 'Host::Base' ORDER BY config_groups.name
SQL (0.5ms)  SELECT "config_group_classes"."puppetclass_id" FROM "config_group_classes" WHERE 1=0
SQL (0.6ms)  SELECT "hostgroup_classes"."puppetclass_id" FROM "hostgroup_classes" WHERE "hostgroup_classes".
"hostgroup_id" IN (3, 1, 2)
HostClass Load (0.5ms)  SELECT "host_classes".* FROM "host_classes" WHERE "host_classes"."host_id" = 1
SQL (1.1ms)  SELECT DISTINCT puppetclasses.id FROM "puppetclasses" INNER JOIN "environment_classes" ON "pupp
etclasses"."id" = "environment_classes"."puppetclass_id" WHERE "environment_classes"."environment_id" = 1 AND
"puppetclasses"."id" IN (115, 410, 404)
SQL (2.6ms)  SELECT "lookup_keys"."id" AS t0_r0, "lookup_keys"."key" AS t0_r1, "lookup_keys"."created_at" AS
t0_r2, "lookup_keys"."updated_at" AS t0_r3, "lookup_keys"."puppetclass_id" AS t0_r4, "lookup_keys"."default_v
alue" AS t0_r5, "lookup_keys"."path" AS t0_r6, "lookup_keys"."description" AS t0_r7, "lookup_keys"."validator_
type" AS t0_r8, "lookup_keys"."validator_rule" AS t0_r9, "lookup_keys"."key_type" AS t0_r10, "lookup_keys"."ov
erride" AS t0_r11, "lookup_keys"."required" AS t0_r12, "lookup_keys"."lookup_values_count" AS t0_r13, "lookup_
keys"."merge_overrides" AS t0_r14, "lookup_keys"."avoid_duplicates" AS t0_r15, "lookup_keys"."use_puppet_defau
lt" AS t0_r16, "lookup_keys"."type" AS t0_r17, "lookup_keys"."merge_default" AS t0_r18, "environment_classes".
"id" AS t1_r0, "environment_classes"."puppetclass_id" AS t1_r1, "environment_classes"."environment_id" AS t1_r
2, "environment_classes"."puppetclass_lookup_key_id" AS t1_r3 FROM "lookup_keys" INNER JOIN "environment_class
```

```

es" ON "environment_classes"."puppetclass_lookup_key_id" = "lookup_keys"."id" WHERE "lookup_keys"."override" =
't' AND "lookup_keys"."type" IN ('PuppetclassLookupKey') AND "environment_classes"."puppetclass_id" IN (115,
404, 410) AND "environment_classes"."environment_id" = 1 ORDER BY lookup_keys.key
Setting Load (0.5ms) SELECT "settings".* FROM "settings" WHERE "settings"."name" = 'Default_variables_Looku
p_Path' ORDER BY name LIMIT 1
Nic::Base Load (0.9ms) SELECT "nics".* FROM "nics" WHERE "nics"."host_id" = 1 ORDER BY identifier
Domain Load (0.9ms) SELECT "domains".* FROM "domains" WHERE "domains"."id" = 1 ORDER BY domains.name LIMIT
1
Setting Load (0.5ms) SELECT "settings".* FROM "settings" WHERE "settings"."name" = 'host_group_matchers_inh
eritance' ORDER BY name LIMIT 1
OperatingSystem Load (0.9ms) SELECT "operatingsystems".* FROM "operatingsystems" WHERE "operatingsystems"."
id" = 1 ORDER BY title LIMIT 1
SQL (3.2ms) SELECT "lookup_values"."id" AS t0_r0, "lookup_values"."match" AS t0_r1, "lookup_values"."value"
AS t0_r2, "lookup_values"."lookup_key_id" AS t0_r3, "lookup_values"."created_at" AS t0_r4, "lookup_values"."u
pdated_at" AS t0_r5, "lookup_values"."use_puppet_default" AS t0_r6, "lookup_keys"."id" AS t1_r0, "lookup_keys"
."key" AS t1_r1, "lookup_keys"."created_at" AS t1_r2, "lookup_keys"."updated_at" AS t1_r3, "lookup_keys"."pupp
etclass_id" AS t1_r4, "lookup_keys"."default_value" AS t1_r5, "lookup_keys"."path" AS t1_r6, "lookup_keys"."de
scription" AS t1_r7, "lookup_keys"."validator_type" AS t1_r8, "lookup_keys"."validator_rule" AS t1_r9, "lookup
_keys"."key_type" AS t1_r10, "lookup_keys"."override" AS t1_r11, "lookup_keys"."required" AS t1_r12, "lookup_k
eys"."lookup_values_count" AS t1_r13, "lookup_keys"."merge_overrides" AS t1_r14, "lookup_keys"."avoid_duplicat
es" AS t1_r15, "lookup_keys"."use_puppet_default" AS t1_r16, "lookup_keys"."type" AS t1_r17, "lookup_keys"."me
rge_default" AS t1_r18 FROM "lookup_values" LEFT OUTER JOIN "lookup_keys" ON "lookup_keys"."id" = "lookup_valu
es"."lookup_key_id" WHERE "lookup_values"."match" IN ('fqdn=cfg01.atl.dealnews.net', 'hostgroup=Production Env
ironment/ATL/server_type_production', 'hostgroup=Production Environment/ATL', 'hostgroup=Production Environmen
t', 'os=Ubuntu 14.04', 'domain=atl.dealnews.net') AND "lookup_values"."lookup_key_id" IN (SELECT "lookup_keys"
."id" FROM "lookup_keys" INNER JOIN "environment_classes" ON "environment_classes"."puppetclass_lookup_key_id"
= "lookup_keys"."id" WHERE "lookup_keys"."override" = 't' AND "lookup_keys"."type" IN ('PuppetclassLookupKey'
) AND "environment_classes"."puppetclass_id" IN (115, 404, 410) AND "environment_classes"."environment_id" = 1
ORDER BY lookup_keys.key) AND "lookup_values"."use_puppet_default" = 'f'
=> {1102=>{"puppet_service_name"=>{:value=>"puppetserver", :element=>"fqdn", :element_name=>"cfg01.atl.dealnew
s.net"}}, 1096=>{"strict_validation"=>{:value=>false, :element=>"fqdn", :element_name=>"cfg01.atl.dealnews.net
"}}}}

```

I suspect that Tomer is right, though.

#### #6 - 10/29/2015 10:14 AM - Michael Eklund

missed the last debug command

```

=> [#<LookupValue id: 5, match: "fqdn=cfg01.atl.dealnews.net", value: "puppetserver", lookup_key_id: 1102, cre
ated_at: "2015-10-28 22:29:25", updated_at: "2015-10-28 22:29:25", use_puppet_default: false>, #<LookupValue i
d: 4, match: "fqdn=cfg01.atl.dealnews.net", value: false, lookup_key_id: 1096, created_at: "2015-10-28 22:24:1
2", updated_at: "2015-10-28 22:24:12", use_puppet_default: false>]

```

#### #7 - 10/29/2015 10:18 AM - Dominic Cleal

Ah good, that confirms to me that Tomer's spot on - it's picking up the override OK internally. Thanks both!

#### #8 - 10/29/2015 01:02 PM - Ori Rabin

- Status changed from Ready For Testing to Closed

- % Done changed from 0 to 100

Applied in changeset [28a5d0bb293d1ab2e8f171910b19f1deed2d79cb](#).