

## Installer - Feature #12955

### formean-installer should set appropriate selinux booleans for IPA authentication

12/29/2015 06:13 PM - Tommy McNeely

<b>Status:</b> Resolved	
<b>Priority:</b> Normal	
<b>Assignee:</b>	
<b>Category:</b>	
<b>Target version:</b>	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b>	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	
<b>Description</b>	
<p>The formean-installer should set appropriate selinux booleans based on settings, for example, if IPA authentication is "enabled" it should set the following:</p> <pre>... setsebool -P allow_httpd_mod_auth_pam on setsebool -P httpd_dbus_sssd on ...</pre> <p>(via puppet modules of course)</p> <p>This is already documented <a href="http://theforeman.org/manuals/1.10/index.html#5.7.3KerberosSingleSign-On">http://theforeman.org/manuals/1.10/index.html#5.7.3KerberosSingleSign-On</a> ... but the installer should take care of it.</p>	

#### History

#1 - 10/06/2017 12:16 PM - Ewoud Kohl van Wijngaarden

- Status changed from New to Resolved

This was fixed in 378d602424da89f4493767949d534b66942db8e2 and included in 2.1.3.