

Installer - Feature #12955

formean-installer should set appropriate selinux booleans for IPA authentication

12/29/2015 06:13 PM - Tommy McNeely

<div><div>Status:</div><div>Resolved</div></div> <div><div>Priority:</div><div>Normal</div></div> <div><div>Assignee:</div><div></div></div> <div><div>Category:</div><div></div></div> <div><div>Target version:</div><div></div></div> <div><div>Difficulty:</div><div></div></div> <div><div>Triaged:</div><div></div></div> <div><div>Bugzilla link:</div><div></div></div> <div><div>Pull request:</div><div></div></div>	<div><div>Fixed in Releases:</div><div></div></div> <div><div>Found in Releases:</div><div></div></div> <div><div>Red Hat JIRA:</div><div></div></div>
<div><div>Description</div><div><p>The formean-installer should set appropriate selinux booleans based on settings, for example, if IPA authentication is "enabled" it should set the following:</p><pre>''' setsebool -P allow_httpd_mod_auth_pam on setsebool -P httpd_dbus_sssd on '''</pre><p>(via puppet modules of course)</p><p>This is already documented http://theforeman.org/manuals/1.10/index.html#5.7.3KerberosSingleSign-On ... but the installer should take care of it.</p></div></div>	

History

#1 - 10/06/2017 12:16 PM - Ewoud Kohl van Wijngaarden

- Status changed from New to Resolved

This was fixed in 378d602424da89f4493767949d534b66942db8e2 and included in 2.1.3.