

## Installer - Bug #13042

### TFTP proxy should create dirs for ZTP and POAP config files

01/07/2016 07:43 AM - Fernando Carolo

<b>Status:</b> Closed	
<b>Priority:</b> Normal	
<b>Assignee:</b> Fernando Carolo	
<b>Category:</b> Foreman modules	
<b>Target version:</b> 1.11.0	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b>	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	
<b>Description</b>	
When the TFTP proxy is installed, it creates 'boot' and 'pxelinux.cfg' subdirectories under tftproot. Support for ZTP (for JunOS hosts) and POAP (for Cisco NX-OS) hosts require two extra directories that are not automatically created by the installer.	

#### History

##### #1 - 01/08/2016 07:10 AM - Dominic Cleal

- Status changed from New to Closed
- % Done changed from 0 to 100
- translation missing: en.field\_release set to 71

Fixed in

[http://projects.theforeman.org/projects/puppet-foreman/repository/puppet-foreman\\_proxy/revisions/12f7081c2602dafb9ae94ffe38e27585d29fb400](http://projects.theforeman.org/projects/puppet-foreman/repository/puppet-foreman_proxy/revisions/12f7081c2602dafb9ae94ffe38e27585d29fb400)  
with the wrong ticket number.