Foreman - Bug #13773

The ssh provisioning uses the Ruby#timeout interface, which is considered a pretty dangerous thing to do

02/17/2016 11:53 AM - Ivan Necas

Status:	New		
Priority:	Normal		
Assignee:			
Category:	Orchestration		
Target version:			
Difficulty:		**Fixed in Releases:**	
Triaged:		**Found in Releases:**	
Bugzilla link:		**Red Hat JIRA:**	
Pull request:			

Description

Some explanations for this not being a good idea:

https://coderwall.com/p/1novga/ruby-timeouts-are-dangerous
http://www.mikeperham.com/2015/05/08/timeout-rubys-most-dangerous-api/
http://blog.headius.com/2008/02/ruby-threadraise-threadkill-timeoutrb.html

Related issues:

Related to Foreman - Tracker #14002: Orchestration build around ActiveRecord ...	**New**	**03/02/2016**

History

#1 - 02/17/2016 11:53 AM - Ivan Necas

- *Subject changed from The ssh provisioning uses the Ruby#timeout interface, which is considered as pretty dangerous thing to do to The ssh provisioning uses the Ruby#timeout interface, which is considered a pretty dangerous thing to do*

#2 - 03/02/2016 04:14 AM - Ivan Necas

- *Related to Tracker #14002: Orchestration build around ActiveRecord hooks tracker added*