

Foreman - Bug #13872

Error accessing default template when trying to disable build mode with a normal user

02/24/2016 06:15 AM - Julien Pivotto

Status: New	
Priority: Normal	
Assignee:	
Category: Organizations and Locations	
Target version:	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases: 1.10.1
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description	
<pre>\$ curl -s -k -u jenkins:pass -H Content-Type:application/json -H Accept:version=2,application/json -X PUT -d '{"build":false}' https://foreman.example.lab/api/hosts/fna060.be.example.lab</pre>	
<pre>{ "error": {"id":435,"errors":{"base":["Failed to generate PXELinux template: undefined method `encoding' for nil:NilClass"]},"full_messages":["Failed to generate PXELinux template: undefined method `encoding' for nil:NilClass"]} }</pre>	
Additional infos:	
<ul style="list-style-type: none">• jenkins is a non admin user• '{"build":true}' works to put the host in build mode• At the end the host is still in build mode• It is broken in the webui as well	

History

#1 - 02/24/2016 06:15 AM - Julien Pivotto

- File production.log added

- Description updated

#2 - 02/24/2016 06:16 AM - Julien Pivotto

- Description updated

#3 - 02/24/2016 06:18 AM - Julien Pivotto

- Category set to API

#4 - 02/24/2016 06:18 AM - Julien Pivotto

- Description updated

#5 - 02/24/2016 06:20 AM - Julien Pivotto

- Subject changed from Error when trying to disable build mode via the API to Error when trying to disable build mode with a normal user

- Description updated

- Category deleted (API)

#6 - 02/24/2016 06:22 AM - Dominic Cleal

Do you have a template named (precisely) "PXELinux default local boot"? If using orgs/locs, it may need to be accessible to the jenkins user too.

#7 - 02/24/2016 06:25 AM - Julien Pivotto

Yes.

And it is not accessible by that user because not associated with any location/org.

#8 - 02/24/2016 06:26 AM - Dominic Cleal

- Subject changed from *Error when trying to disable build mode with a normal user* to *Error accessing default template when trying to disable build mode with a normal user*

- Category set to *Organizations and Locations*

#9 - 02/24/2016 06:27 AM - Julien Pivotto

- Subject changed from *Error accessing default template when trying to disable build mode with a normal user* to *Error when trying to disable build mode with a normal user*

- Category deleted (*Organizations and Locations*)

Fixed, thanks Dominic.

Not sure if this is a bug or not, but I would have expected that a user would have been able to disable build on a host "out of the box".

#10 - 02/24/2016 06:28 AM - Julien Pivotto

- Subject changed from *Error when trying to disable build mode with a normal user* to *Error accessing default template when trying to disable build mode with a normal user*

- Category set to *Organizations and Locations*

#11 - 02/24/2016 06:35 AM - Dominic Cleal

No problem. It's definitely a bug, the user shouldn't need direct permissions to view those templates as they're hard-coded. It can probably be fixed just by using `ProvisioningTemplate.unscoped` over at <https://github.com/foreman/foreman/blob/1.10.2/app/models/concerns/orchestration/tftp.rb#L48-L50> which will avoid orgs/locs entirely.

The code should probably be more defensive if they're missing so as not to get the 'encoding' related error, e.g. https://github.com/foreman/foreman/blob/1.10.2/app/models/provisioning_template.rb#L116

Files

production.log	15.8 KB	02/24/2016	Julien Pivotto
----------------	---------	------------	----------------