

Foreman - Refactor #13978

Replace AR connection value_to_boolean method with Foreman::Cast

03/01/2016 09:04 AM - Dominic Cleal

Status: Closed	
Priority: Normal	
Assignee: Dominic Cleal	
Category: Rails	
Target version: 1.12.0	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request: https://github.com/foreman/foreman/pull/3276	
Description	
The host common #lookup_values_attributes= method uses an internal Active Record method value_to_boolean to parse the _destroy parameter from the nested attributes supplied by the UI.	
https://github.com/foreman/foreman/blob/1.11.0-RC1/app/models/concerns/host_common.rb#L54-L58	
This method has been moved in Rails 4.2 and since it's really rather internal, it should be replaced by Foreman::Cast.to_bool or similar.	
Related issues:	
Blocks Foreman - Feature #13244: Upgrade Ruby on Rails to 4.2	Closed 01/15/2016

Associated revisions

Revision 904367f1 - 03/06/2016 08:31 AM - Dominic Cleal

fixes #13978 - replace AR value_to_boolean with our caster

In Rails 4.2, value_to_boolean was moved further into ActiveRecord's column type classes. Replace the use of this internal method with Foreman's own well-tested caster.

History

#1 - 03/01/2016 09:04 AM - Dominic Cleal

- Blocks Feature #13244: Upgrade Ruby on Rails to 4.2 added

#2 - 03/04/2016 08:25 AM - The Foreman Bot

- Status changed from New to Ready For Testing

- Assignee set to Dominic Cleal

- Pull request <https://github.com/foreman/foreman/pull/3276> added

#3 - 03/06/2016 09:01 AM - Dominic Cleal

- Status changed from Ready For Testing to Closed

- % Done changed from 0 to 100

Applied in changeset [904367f1e2da6738d11dc5231c0a91fdcf088c6f](https://github.com/foreman/foreman/commit/904367f1e2da6738d11dc5231c0a91fdcf088c6f).

#4 - 03/07/2016 03:40 AM - Dominic Cleal

- translation missing: en.field_release set to 136