

Foreman - Bug #13982

API description for creating hosts incorrectly lists "interfaces_attributes"s "primary" as optional

03/01/2016 10:57 AM - Pieter Hollants

Status: Duplicate	
Priority: High	
Assignee:	
Category: API	
Target version:	
Difficulty: easy	Fixed in Releases:
Triaged:	Found in Releases: 1.9.3
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description	
<p>http://theforeman.org/api/1.10/apidoc/v2/hosts/create.html says:</p> <pre>host[interfaces_attributes][primary] optional , nil allowed</pre> <p>The "optional" flag seems to be wrong:</p> <pre>\$ curl -s -H "Content-Type: application/json" k -u admin:secret -d '{"host":{"hostgroup_id": "1", "name": "test", "environment_id":"1", "interfaces_attributes":{"0":{"ip":"192.168.100.5","mac":"00:11:22:33:44:55","type":"interface","identifier":"eth0"}}}' http://foreman.test.foo/api/hosts { "error": {"id":null,"errors":{"interfaces.mac":["can't be blank"],"full_messages":["Mac can't be blank"]} } \$ curl -s -H "Content-Type: application/json" k -u admin:secret -d '{"host":{"hostgroup_id": "1", "name": "test", "environment_id":"1", "interfaces_attributes":{"0":{"ip":"192.168.100.5","mac":"00:11:22:33:44:55","primary":"true"}}}' http://foreman.test.foo/api/hosts {"ip":"192.168.100.5", ... ,"all_puppetclasses":[]}</pre>	
Related issues:	
Is duplicate of Foreman - Bug #14239: Creating a host via API fails with crypt...	Closed 03/16/2016

History

#1 - 03/18/2016 05:17 AM - Dominic Cleal

- Is duplicate of Bug #14239: Creating a host via API fails with cryptic error when no primary interface is set explicitly added

#2 - 03/18/2016 05:18 AM - Dominic Cleal

- Status changed from New to Duplicate

I think [#14239](#) has fixed this in a different way, by automatically setting a primary interface if none is specified. The attribute remains optional. Thanks for the report.