

## Foreman - Feature #14030

### Associate IPMI interfaces with domains and subnets

03/02/2016 06:27 PM - Alan Evans

<b>Status:</b> Rejected	
<b>Priority:</b> Normal	
<b>Assignee:</b>	
<b>Category:</b> BMC	
<b>Target version:</b>	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b>	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	
<b>Description</b> It seems that IPMI interfaces don't get tied to subnets and domains the way the primary interface does. (Does foreman do other interfaces?)  It would be nice to have the subnet/domain associated automatically.	

#### History

---

**#1 - 03/03/2016 03:19 AM - Dominic Cleal**

- *Category set to BMC*

- *Status changed from New to Need more information*

You can set a subnet and domain for a BMC/IPMI interface under the interface settings when editing a host. Is there something else you mean?

**#2 - 03/03/2016 03:51 AM - Marek Hulán**

I guess this is more about facts importing and auto-association?

**#3 - 05/17/2017 03:25 PM - Anonymous**

- *Status changed from Need more information to Rejected*

no reaction, closing