

## Foreman - Feature #14245

### Create new template helper setting('global\_setting\_name')

03/17/2016 03:31 AM - Lukas Zapletal

<b>Status:</b> New	
<b>Priority:</b> Normal	
<b>Assignee:</b> Lukas Zapletal	
<b>Category:</b> Templates	
<b>Target version:</b>	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b>	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	
<b>Description</b>	
That can be used to activate discovery in Global PXE default when it's active. This is generic enough to be used in other cases.	
<b>Related issues:</b>	
Related to Foreman - Feature #7828: Provide base URL of Foreman via foreman_url	<b>Duplicate</b> 10/07/2014

#### History

##### #1 - 03/17/2016 03:31 AM - Lukas Zapletal

- Related to Feature #7828: Provide base URL of Foreman via foreman\_url added

##### #2 - 03/17/2016 03:42 AM - Marek Hulán

We already have [Setting something](#) which is forbidden in safe mode since settings can contain sensitive information (e.g. default root password, oauth secrets etc). Or would you like to allow just whitelisted settings?

##### #3 - 03/17/2016 08:39 AM - Bryan Kearney

- Bugzilla link set to 1176111

##### #4 - 03/17/2016 01:03 PM - Lukas Zapletal

Yeah my idea was to whitelist them.

##### #5 - 03/18/2016 08:23 AM - Marek Hulán

ok, then +1 :-)

##### #6 - 03/21/2016 06:52 AM - Lukas Zapletal

- Bugzilla link deleted (1176111)