

## Foreman - Bug #14541

### foreman-rake must preserve environment variables

04/08/2016 04:23 AM - Jérôme Vizcaino

<b>Status:</b>	Closed	
<b>Priority:</b>	Normal	
<b>Assignee:</b>		
<b>Category:</b>	Rake tasks	
<b>Target version:</b>	1.12.0	
<b>Difficulty:</b>		<b>Fixed in Releases:</b>
<b>Triaged:</b>		<b>Found in Releases:</b> 1.9.3
<b>Bugzilla link:</b>		<b>Red Hat JIRA:</b>
<b>Pull request:</b>	<a href="https://github.com/foreman/foreman/pull/3534">https://github.com/foreman/foreman/pull/3534</a>	
<b>Description</b>		
<p>Calling foreman-rake db:seed fills the database with default entries. Of these seeds, 04-admin.rb takes care of adding the default admin account. This can be configured using SEED_ADMIN_* environment variables but calling foreman-rake with id != foreman fails.</p> <p>Looking at foreman-rake, the su call misses the -p flag, so environment is dropped when changing user.</p>		

#### Associated revisions

##### Revision 9fd99121 - 05/24/2016 11:42 AM - Stijn Tintel

Fixes #14541 - foreman-rake must preserve environment variables

Signed-off-by: Stijn Tintel <[stijn@linux-ipv6.be](mailto:stijn@linux-ipv6.be)>

#### History

##### #1 - 04/08/2016 04:28 AM - Dominic Cleal

- Category set to Rake tasks

##### #2 - 05/18/2016 06:56 AM - The Foreman Bot

- Status changed from New to Ready For Testing

- Pull request <https://github.com/foreman/foreman/pull/3533> added

##### #3 - 05/18/2016 07:17 AM - Stijn Tintel

Adding -p to the su call is unfortunately not an option:

```
root@foreman:~# /usr/sbin/foreman-rake db:seed
-su: /root/.bash_profile: Permission denied
rake aborted!
Errno::EACCES: Permission denied - /root/.factor/facts.d
/usr/share/foreman/vendor/ruby/2.0.0/gems/facter-1.7.6/lib/facter/util/directory_loader.rb:75:in `open'
/usr/share/foreman/vendor/ruby/2.0.0/gems/facter-1.7.6/lib/facter/util/directory_loader.rb:75:in `entries'
/usr/share/foreman/vendor/ruby/2.0.0/gems/facter-1.7.6/lib/facter/util/directory_loader.rb:75:in `entries'
/usr/share/foreman/vendor/ruby/2.0.0/gems/facter-1.7.6/lib/facter/util/directory_loader.rb:55:in `load'
/usr/share/foreman/vendor/ruby/2.0.0/gems/facter-1.7.6/lib/facter/util/composite_loader.rb:10:in `block in load'
/usr/share/foreman/vendor/ruby/2.0.0/gems/facter-1.7.6/lib/facter/util/composite_loader.rb:10:in `each'
/usr/share/foreman/vendor/ruby/2.0.0/gems/facter-1.7.6/lib/facter/util/composite_loader.rb:10:in `load'
/usr/share/foreman/vendor/ruby/2.0.0/gems/facter-1.7.6/lib/facter/util/collection.rb:154:in `load_external_facts'
/usr/share/foreman/vendor/ruby/2.0.0/gems/facter-1.7.6/lib/facter/util/collection.rb:110:in `load'
/usr/share/foreman/vendor/ruby/2.0.0/gems/facter-1.7.6/lib/facter/util/collection.rb:84:in `fact'
/usr/share/foreman/vendor/ruby/2.0.0/gems/facter-1.7.6/lib/facter/util/collection.rb:140:in `value'
/usr/share/foreman/vendor/ruby/2.0.0/gems/facter-1.7.6/lib/facter.rb:112:in `block (2 levels) in singleton class'
/usr/share/foreman/app/models/setting/general.rb:7:in `load_defaults'
```

```

/usr/share/foreman/config/initializers/foreman.rb:21:in `each'
/usr/share/foreman/config/initializers/foreman.rb:21:in `'
/usr/share/foreman/vendor/ruby/2.0.0/gems/activestorage-4.1.14.2/lib/active_storage/dependencies.rb:241:in `load'
/usr/share/foreman/vendor/ruby/2.0.0/gems/activestorage-4.1.14.2/lib/active_storage/dependencies.rb:241:in `block in load'
/usr/share/foreman/vendor/ruby/2.0.0/gems/activestorage-4.1.14.2/lib/active_storage/dependencies.rb:232:in `load_dependency'
/usr/share/foreman/vendor/ruby/2.0.0/gems/activestorage-4.1.14.2/lib/active_storage/dependencies.rb:241:in `load'
/usr/share/foreman/vendor/ruby/2.0.0/gems/railties-4.1.14.2/lib/rails/engine.rb:648:in `block in load_config_initializer'
/usr/share/foreman/vendor/ruby/2.0.0/gems/activestorage-4.1.14.2/lib/active_storage/notifications.rb:161:in `instrument'
/usr/share/foreman/vendor/ruby/2.0.0/gems/railties-4.1.14.2/lib/rails/engine.rb:647:in `load_config_initializer'
/usr/share/foreman/vendor/ruby/2.0.0/gems/railties-4.1.14.2/lib/rails/engine.rb:612:in `block (2 levels) in <class:Engine>'
/usr/share/foreman/vendor/ruby/2.0.0/gems/railties-4.1.14.2/lib/rails/engine.rb:611:in `each'
/usr/share/foreman/vendor/ruby/2.0.0/gems/railties-4.1.14.2/lib/rails/engine.rb:611:in `block in <class:Engine>'
/usr/share/foreman/vendor/ruby/2.0.0/gems/railties-4.1.14.2/lib/rails/initializable.rb:30:in `instance_exec'
/usr/share/foreman/vendor/ruby/2.0.0/gems/railties-4.1.14.2/lib/rails/initializable.rb:30:in `run'
/usr/share/foreman/vendor/ruby/2.0.0/gems/railties-4.1.14.2/lib/rails/initializable.rb:55:in `block in run_initializers'
/usr/share/foreman/vendor/ruby/2.0.0/gems/railties-4.1.14.2/lib/rails/initializable.rb:44:in `each'
/usr/share/foreman/vendor/ruby/2.0.0/gems/railties-4.1.14.2/lib/rails/initializable.rb:44:in `tsort_each_child'
/usr/share/foreman/vendor/ruby/2.0.0/gems/railties-4.1.14.2/lib/rails/initializable.rb:54:in `run_initializers'
/usr/share/foreman/vendor/ruby/2.0.0/gems/railties-4.1.14.2/lib/rails/application.rb:300:in `initialize!'
/usr/share/foreman/vendor/ruby/2.0.0/gems/railties-4.1.14.2/lib/rails/railtie.rb:194:in `public_send'
/usr/share/foreman/vendor/ruby/2.0.0/gems/railties-4.1.14.2/lib/rails/railtie.rb:194:in `method_missing'
/usr/share/foreman/config/environment.rb:5:in `'
/usr/share/foreman/vendor/ruby/2.0.0/gems/polyglot-0.3.5/lib/polyglot.rb:65:in `require'
/usr/share/foreman/vendor/ruby/2.0.0/gems/polyglot-0.3.5/lib/polyglot.rb:65:in `require'
/usr/share/foreman/vendor/ruby/2.0.0/gems/activestorage-4.1.14.2/lib/active_storage/dependencies.rb:247:in `block in require'
/usr/share/foreman/vendor/ruby/2.0.0/gems/activestorage-4.1.14.2/lib/active_storage/dependencies.rb:232:in `load_dependency'
/usr/share/foreman/vendor/ruby/2.0.0/gems/activestorage-4.1.14.2/lib/active_storage/dependencies.rb:247:in `require'
/usr/share/foreman/vendor/ruby/2.0.0/gems/railties-4.1.14.2/lib/rails/application.rb:276:in `require_environment!'
/usr/share/foreman/vendor/ruby/2.0.0/gems/railties-4.1.14.2/lib/rails/application.rb:405:in `block in run_tasks_blocks'
/usr/share/foreman/vendor/ruby/2.0.0/gems/activerecord-4.1.14.2/lib/active_record/railties/databases.rake:173:in `block (2 levels) in <top (required)>'
/usr/bin/rake2.0:37:in `'
Tasks: TOP => db:abort_if_pending_migrations => environment
(See full trace by running task with --trace)

```

#### #4 - 05/18/2016 07:18 AM - Dominic Cleal

- Status changed from Ready For Testing to New
- Pull request deleted (<https://github.com/foreman/foreman/pull/3533>)

HOME might be carried through with -p?

#### #5 - 05/18/2016 08:26 AM - Stijn Tintel

This is just a warning and can be ignored:

```
-su: /root/.bash_profile: Permission denied
```

But the problem seems to be in the facter gem, in /usr/share/foreman/vendor/ruby/2.0.0/gems/facter-1.7.6/lib/facter/util/config.rb:

```

def self.external_facts_dirs
  if Facter::Util::Root.root?
    windows_dir = windows_data_dir
    if windows_dir.nil? then
      ["/etc/facter/facts.d", "/etc/puppetlabs/facter/facts.d"]
    end
  end
end

```

```
else
  [File.join(windows_dir, 'PuppetLabs', 'factor', 'facts.d')]
end
else
  [File.expand_path(File.join("~", ".factor", "facts.d"))]
end
end
```

So with the -p option, the environment contains HOME=/root, which is causing the above problem.

**#6 - 05/18/2016 09:25 AM - The Foreman Bot**

- Status changed from New to Ready For Testing
- Pull request <https://github.com/theforeman/foreman/pull/3534> added

**#7 - 05/24/2016 12:01 PM - Anonymous**

- Status changed from Ready For Testing to Closed
- % Done changed from 0 to 100

Applied in changeset [9fd991210db89b693cb17fa2c25c8104f8981b16](#).

**#8 - 05/25/2016 03:10 AM - Dominic Cleal**

- translation missing: en.field\_release set to 136