

Foreman - Bug #14542

foreman-rake db:setup fails in db:seed task

04/08/2016 04:30 AM - Jérôme Vizcaino

Status: New	
Priority: Normal	
Assignee:	
Category: DB migrations	
Target version:	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases: 1.9.3
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description	
Howto reproduce:	
<ul style="list-style-type: none">• start from scratch, install the foreman package with any database support (sqlite will do)• as root, call foreman-rake db:setup : the program fails during the db:seed task, specifically in the 04-admin.rb part (the backtrace stipulates that it can't call dup in NilClass at 04-admin.rb:38)	
Cause:	
<ul style="list-style-type: none">• this is partly related to #14541 because none of ENV['SEED_ADMIN_EMAIL'] nor Setting[:administrator] seem to be valid	
As a sidenote, calling foreman-rake db:seed works.	

History

#1 - 04/08/2016 04:34 AM - Dominic Cleal

- Category set to DB migrations

Setting[:administrator] won't have been initialised yet, as there's been no application startup since the DB migration and before the DB seed. Running migration/creation and seeding in two separate commands works as the setting's populated when the seed starts up.

In the long term, settings should probably be moved into the seed scripts.