

## Foreman - Bug #1502

### A subnet without TFTP set makes foreman unable to set a host in build.

02/23/2012 01:23 PM - Ashley Penney

<b>Status:</b> Duplicate	
<b>Priority:</b> Normal	
<b>Assignee:</b>	
<b>Category:</b>	
<b>Target version:</b>	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b>	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	
<b>Description</b>	
<p>We have a situation where we need to set hosts to build but we cannot use DHCP/TFTP and instead use a boot.iso to pass the params into boot: by hand. We do however require the kickstart from foreman. As it stands if you put a machine in a subnet that has no TFTP assigned Foreman will attempt to write the TFTP stuff locally and fail to set build:</p> <p>Processing HostsController#setBuild (for 10.45.62.4 at 2012-02-23 18:20:03) [GET] Parameters: {"action"=&gt;"setBuild", "id"=&gt;"per5-puppet-test.usa.net", "controller"=&gt;"hosts"} <b>DEPRECATION WARNING*</b> Managing TFTP without a smart-proxy will not be supported in the next release TFTP Failed: Permission denied - RedHat-5.7-x86_64 or /usr/share/foreman//01-00-0c-29-dd-10-0b Failed to save: Redirected to <a href="https://foreman.sys.perimeterusa.com/hosts/per5-puppet-test.usa.net">https://foreman.sys.perimeterusa.com/hosts/per5-puppet-test.usa.net</a> Completed in 15ms (DB: 9)   302 Found [<a href="https://foreman.sys.perimeterusa.com/hosts/per5-puppet-test.usa.net/setBuild">https://foreman.sys.perimeterusa.com/hosts/per5-puppet-test.usa.net/setBuild</a>]</p> <p>If tftp is not set then don't try to write any TFTP stuff. :)</p>	

### History

#1 - 02/23/2012 01:48 PM - Ashley Penney

Looks like a duplicate of <http://www.theforeman.org/issues/1376> - didn't spot it when looking earlier, sorry!

#2 - 06/18/2013 11:18 AM - Benjamin Papillon

- Status changed from New to Duplicate