

Smart Proxy - Bug #15110

Default setting values used for module initialization aren't being marked as "default" when they are logged.

05/20/2016 08:30 AM - Anonymous

Status: Closed	
Priority: Normal	
Assignee:	
Category: Core	
Target version: 1.12.0	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request: https://github.com/theforeman/smart-proxy/pull/421	
Description	
Related issues:	
Related to Smart Proxy - Refactor #14618: Refactor plugin initialization and ...	Closed 04/13/2016

Associated revisions

Revision [dd2fc60c](#) - 05/23/2016 07:44 AM - Dmitri Dolguikh

Fixes #15110 - used default setting values are marked now.

History

#1 - 05/20/2016 08:32 AM - The Foreman Bot

- Status changed from New to Ready For Testing

- Pull request <https://github.com/theforeman/smart-proxy/pull/421> added

#2 - 05/23/2016 07:45 AM - Dominic Cleal

- Related to Refactor #14618: Refactor plugin initialization and loading added

#3 - 05/23/2016 07:45 AM - Dominic Cleal

- translation missing: en.field_release set to 136

e.g.

```
D, [2016-05-23T12:43:14.295760 #32091] DEBUG -- : 'dns' settings: 'dns_ttl': 86400 (default), 'enabled': true, 'use_provider': dns_libvirt
```

#4 - 05/23/2016 08:01 AM - Anonymous

- Status changed from Ready For Testing to Closed

- % Done changed from 0 to 100

Applied in changeset [dd2fc60c724217e3517d5ac07683e32152960b7c](#).