

Smart Proxy - Bug #15130

Puppet environment retriever set to config_file, not API when using "environmentpath"

05/23/2016 03:25 AM - Dominic Cleal

Status:	Closed	
Priority:	Normal	
Assignee:		
Category:	Puppet	
Target version:	1.12.0	
Difficulty:		Fixed in Releases:
Triaged:		Found in Releases: Nightly
Bugzilla link:		Red Hat JIRA:
Pull request:	https://github.com/foreman-smart-proxy/pull/422	

Description

On a Puppet 3.8.7 installation using directory environments (and environmentpath), the config file environment retriever is being selected instead of the API retriever.

```
D, [2016-05-23T07:21:38.659910 #10700] DEBUG -- : 'puppet' settings: 'enabled': https, 'puppet_version': 3.8.7, 'use_provider': [:puppet_proxy_legacy]
D, [2016-05-23T07:21:38.660065 #10700] DEBUG -- : Providers ['puppet_proxy_legacy'] are going to be configured for 'puppet'
D, [2016-05-23T07:21:39.046652 #10700] DEBUG -- : 'puppet_proxy_legacy' settings: 'classes_retriever': cached_legacy_parser, 'environments_retriever': config_file, 'puppet_conf': /etc/puppet/puppet.conf, 'puppet_ssl_ca': /var/lib/puppet/ssl/certs/ca.pem, 'puppet_ssl_cert': /var/lib/puppet/ssl/certs/foreman.example.com.pem, 'puppet_ssl_key': /var/lib/puppet/ssl/private_keys/foreman.example.com.pem, 'puppet_url': https://foreman.example.com:8140, 'puppet_version': 3.8.7, 'use_cache': true, 'use_provider': [:puppet_proxy_legacy]
...
W, [2016-05-23T07:20:37.269494 #8521] WARN -- : No environments found - falling back to defaults (production - /etc/puppet/modules)
I, [2016-05-23T07:20:37.270246 #8521] INFO -- : 127.0.0.1 -- [23/May/2016:07:20:37 +0000] "GET /puppet/environments HTTP/1.1" 200 14 0.0110

W, [2016-05-23T07:20:37.370079 #8521] WARN -- : No environments found - falling back to defaults (production - /etc/puppet/modules)
I, [2016-05-23T07:20:37.370830 #8521] INFO -- : 127.0.0.1 -- [23/May/2016:07:20:37 +0000] "GET /puppet/environments/production/classes HTTP/1.1" 200 2 0.0140
```

puppet.conf:

```
[main]
# Where Puppet's general dynamic and/or growing data is kept
vardir = /var/lib/puppet

# The Puppet log directory.
# The default value is '$vardir/log'.
logdir = /var/log/puppet

# Where Puppet PID files are kept.
# The default value is '$vardir/run'.
rundir = /var/run/puppet

# Where SSL certificates are kept.
# The default value is '$confdir/ssl'.
ssldir = /var/lib/puppet/ssl

# Allow services in the 'puppet' group to access key (Foreman + proxy)
privatekeydir = $ssldir/private_keys { group = service }
hostprivkey = $privatekeydir/$certname.pem { mode = 640 }
```

```
show_diff      = false

## Server config

reports        = foreman

environmentpath = /etc/puppet/environments
basemodulepath  = /etc/puppet/environments/common:/etc/puppet/modules:/usr/share/puppet/modules

hiera_config    = $confdir/hiera.yaml

[...]
```

Related issues:

Related to Smart Proxy - Feature #13667: puppet_proxy and puppetca modules lo...	Closed	02/11/2016
--	--------	------------

Associated revisions

Revision 185cfbb7 - 05/23/2016 09:07 AM - Dmitri Dolguikh

Fixes #15130 - use puppet apiv2 when 'environmentpath' is present

History

#1 - 05/23/2016 03:26 AM - Dominic Cleal

- Related to Feature #13667: puppet_proxy and puppetca modules load puppet gem in puppet 4.0 and higher environments added

#2 - 05/23/2016 04:36 AM - Anonymous

- Status changed from New to Assigned

- Assignee set to Anonymous

#3 - 05/23/2016 05:29 AM - The Foreman Bot

- Status changed from Assigned to Ready For Testing

- Pull request <https://github.com/foreman/smart-proxy/pull/422> added

#4 - 05/23/2016 10:01 AM - Anonymous

- Status changed from Ready For Testing to Closed

- % Done changed from 0 to 100

Applied in changeset [185cfbb776aa272699895258a8d3e90a3d15dfaa](#).