

Packaging - Bug #1569

Init-Script for RHEL doesnt work

04/10/2012 02:01 AM - David M.

Status: Closed	
Priority: Normal	
Assignee:	
Category:	
Target version:	
Difficulty: trivial	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description	
<p>The Init-RC Script for RHEL on RHEL6 doesnt work if you are not in the foreman-home. If you run /etc/init.d/foreman start from outside of the foreman home you get the error</p> <pre>configuration /config.ru not found</pre> <p>Here is a possible fix for this (maybe someone has a better idea):</p> <pre>--- /opt/foreman/foreman/extras/spec/foreman.init 2012-03-28 14:04:35.828489612 +0100 +++ /etc/init.d/foreman 2012-04-10 05:57:11.827524267 +0100 @@ -23,6 +23,7 @@ start() { echo -n \$"Starting \$prog: " + cd \$FOREMAN_HOME daemon --user \${FOREMAN_USER} /usr/bin/ruby \${FOREMAN_HOME}/script/rails s -p \${FOREMAN_PORT} -e \${FOREMAN_ENV} -d > /dev/null RETVAL=\$? if [\$RETVAL = 0]</pre>	

History

#1 - 05/21/2012 08:49 AM - Ohad Levy

- Category set to Packaging
- Difficulty set to trivial
- Assignee set to Anonymous

#2 - 06/17/2012 06:54 AM - Ohad Levy

- Project changed from Foreman to Packaging
- Category deleted (Packaging)
- Target version deleted (1.0)

#3 - 01/02/2013 09:02 AM - Sam Kottler

- Status changed from New to Closed

I spoke to Jason a few weeks ago about this and it should be resolved. Please re-open the issue if you're still running into problems.