

## Foreman - Feature #15863

### Log request IDs (tagged logging) in production.log

07/27/2016 10:33 AM - Dominic Cleal

<b>Status:</b> Closed	
<b>Priority:</b> Normal	
<b>Assignee:</b> Dominic Cleal	
<b>Category:</b> Logging	
<b>Target version:</b> 1.13.0	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b>	<b>Found in Releases:</b>
<b>Bugzilla link:</b> 1435563	<b>Red Hat JIRA:</b>
<b>Pull request:</b> <a href="https://github.com/foreman/foreman/pull/3678">https://github.com/foreman/foreman/pull/3678</a>	
<b>Description</b>	
Request IDs can be added to Foreman's logs to make it easier to trace all log messages relating to a particular request when they interleave from multiple server processes.	
Rails stores an ID in the request environment by default, and since Rails 5, the default configuration is to log it. The request ID is derived from the X-Request-ID header, otherwise a random UUID. Since Foreman uses the logging gem without tagging support instead of the default Rails logger, implementing this requires passing the extra information to its MDC/NDC (context) storage.	
<b>Related issues:</b>	
Related to Foreman - Feature #15876: Send request and session ids to foreman-...	<b>Duplicate</b> <b>07/28/2016</b>
Related to Foreman - Feature #10982: Add logging to smart proxy requests (Pro...	<b>Closed</b> <b>07/02/2015</b>
Related to Foreman - Bug #19017: Use request id instead of session id of tagg...	<b>Closed</b> <b>03/24/2017</b>

#### Associated revisions

##### Revision d97deb49 - 07/28/2016 04:24 AM - Dominic Cleal

fixes #15863 - add short session or request ID to logs

New middleware stores the session and request IDs (either from X-Request-ID or a UUID generated by Rails) in the logger's thread storage. The truncated session ID is now logged by default to minimise size of the log messages.

#### History

##### #1 - 07/27/2016 10:41 AM - The Foreman Bot

- Status changed from Assigned to Ready For Testing
- Pull request <https://github.com/foreman/foreman/pull/3678> added

##### #2 - 07/28/2016 05:02 AM - Dominic Cleal

- Status changed from Ready For Testing to Closed
- % Done changed from 0 to 100

Applied in changeset [d97deb49dc07939998565bec0cef582082a8d91d](https://github.com/foreman/foreman/commit/d97deb49dc07939998565bec0cef582082a8d91d).

##### #3 - 07/28/2016 07:48 AM - Lukas Zapletal

- Related to Feature #15876: Send request and session ids to foreman-proxy as HTTP headers added

##### #4 - 07/28/2016 07:51 AM - Dominic Cleal

- Related to Feature #10982: Add logging to smart proxy requests (ProxyAPI) added

##### #5 - 07/29/2016 07:19 AM - Dominic Cleal

- translation missing: en.field\_release set to 160

**#6 - 03/24/2017 05:00 AM - Ivan Necas**

- Bugzilla link set to 1435563

**#7 - 03/24/2017 07:42 AM - Ivan Necas**

- Related to Bug #19017: Use request id instead of session id of tagged logging added