

Foreman - Bug #1608

REST API calls /hosts/:id/puppetclasses fails for hosts with no class and no hostgroup

05/09/2012 07:12 AM - Florent Castelli

Status: Duplicate	
Priority: Normal	
Assignee:	
Category:	
Target version:	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description	
Extract from the logs:	
<pre>Hostgroup Load (0.9ms) SELECT DISTINCT puppetclasses.id FROM "hostgroups" INNER JOIN "hosts" ON " hosts"."hostgroup_id" = "hostgroups"."id" INNER JOIN "hostgroups_puppetclasses" ON "hostgroups_pup petclasses"."hostgroup_id" = "hostgroups"."id" INNER JOIN "puppetclasses" ON "puppetclasses"."id" = "hostgroups_puppetclasses"."puppetclass_id" WHERE (hosts.name = 'somehost') Puppetclass Load (0.6ms) SELECT name, id FROM "puppetclasses" WHERE ((puppetclasses.id = 'nil')) PG::Error: ERROR: invalid input syntax for integer: "nil" LINE 1: ..., id FROM "puppetclasses" WHERE ((puppetclasses.id = 'nil')) ^ : SELECT name, id FROM "puppetclasses" WHERE ((puppetclasses.id = 'nil')) Operation FAILED: PG::Error: ERROR: invalid input syntax for integer: "nil" LINE 1: ..., id FROM "puppetclasses" WHERE ((puppetclasses.id = 'nil')) ^ : SELECT name, id FROM "puppetclasses" WHERE ((puppetclasses.id = 'nil')) app/controllers/puppetclasses_controller.rb:22:in `index' app/controllers/puppetclasses_controller.rb:17:in `index' Completed 500 Internal Server Error in 25ms</pre>	
Suggested fix is to change in app/models/puppetclass.rb the condition "puppetclasses.id = 'nil'" to "1=0" to produce a valid false statement. There's maybe a more portable way of producing a false statement, but I know for sure that sqlite doesn't support "false".	
Related issues:	
Has duplicate Foreman - Bug #1609: REST API calls /hosts/:id/puppetclasses fa...	Closed 05/09/2012

History

#1 - 05/09/2012 08:18 AM - Ohad Levy

- Status changed from New to Duplicate