

## Foreman - Bug #162

### Certificate will not be removed when FQDN has uppercase letters

01/29/2010 03:23 PM - Ric Danger

<b>Status:</b> Closed	
<b>Priority:</b> Normal	
<b>Assignee:</b> Ohad Levy	
<b>Category:</b> PuppetCA	
<b>Target version:</b> 0.1-4	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b>	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	
<b>Description</b>	
Hi,	
I found out that puppet certificate will not be removed when the host FQDN has uppercase letters.	
Regards, Ricardo	

#### Associated revisions

##### Revision f1832124 - 01/30/2010 01:17 PM - Ohad Levy

fixes 162 - Certificate will not be removed when FQDN has uppercase letters

#### History

##### #1 - 01/29/2010 03:53 PM - Ric Danger

- % Done changed from 0 to 30

This patch should fix it.

```
diff -rupN vendor/plugins/proxy/lib/proxy.rb vendor/plugins/proxy/lib/proxy.rb
-- vendor/plugins/proxy/lib/proxy.rb 2009-12-14 07:57:25.000000000 0000
++ vendor/plugins/proxy/lib/proxy.rb 2010-01-29 15:48:29.000000000 0000
@ -81,12 +81,12 @ module GW
return false
end
begin
- if (ssldir + "ca/signed/#{fqdn}.pem").file?
if (ssldir + "ca/signed/#{fqdn.downcase}.pem").file?
command = "/usr/bin/sudo S #{@sbin}/puppetca --clean #{fqdn} < /dev/null"
logger.info system(command)
return true
else
logger.warn ssldir + "PuppetCA: ca/signed/#{fqdn}.pem does not exists - skipping"
+ logger.warn ssldir + "PuppetCA: ca/signed/#{fqdn.downcase}.pem does not exists - skipping"
return true
end
rescue StandardError => e
```

##### #2 - 01/29/2010 03:57 PM - Ric Danger

- Status changed from New to Closed

- % Done changed from 30 to 100

##### #3 - 01/29/2010 04:06 PM - Ohad Levy

- Status changed from Closed to New

Hi, its not yet closed as it was not pushed to the repo :)

what about the sign method ? isnt that affected as well?

you could generally do it in a oneliner, something like  
fqdn.downcase! as the first line after the def line.

**#4 - 01/29/2010 04:31 PM - Ric Danger**

Ohad Levy wrote:

Hi, its not yet closed as it was not pushed to the repo :)

what about the sign method ? isnt that affected as well?

you could generally do it in a oneliner, something like  
fqdn.downcase! as the first line after the def line.

Nop.

The problem was that foreman checks for the file on the ssl/signed directory, using the fqdn case.

Puppetca cert files are always lowercase. So, if the case was not matched, foreman would not run puppetca --clean.

Puppetca commands are case-insensitive, so there is no problem here.

**#5 - 01/30/2010 10:34 AM - Ohad Levy**

- *Category set to PuppetCA*
- *Status changed from New to Assigned*
- *Assignee set to Ohad Levy*
- *Target version set to 0.1-4*

**#6 - 01/30/2010 02:24 PM - Ohad Levy**

- *Status changed from Assigned to Ready For Testing*

Applied in changeset [f18321244cd08c2e1688267ca6b374ef6f364267](#).

**#7 - 02/05/2010 04:11 AM - Ohad Levy**

- *Status changed from Ready For Testing to Closed*