

## Foreman - Feature #1647

### Allow reports to be configured so only last report (per host) is displayed

05/23/2012 08:48 AM - Adam Kosmin

<b>Status:</b> New	
<b>Priority:</b> Normal	
<b>Assignee:</b>	
<b>Category:</b> Reporting	
<b>Target version:</b>	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b>	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	
<b>Description</b>	
<p>Of course, this should be optional. Here's my nasty hack to app/views/reports/_list.html.erb which gets the job done for me despite being hard-coded. Ideally, this would be a configuration option somewhere in the roles scope.</p>	
<pre>&lt;% firsts = [] %&gt; &lt;% @reports.each do  report  %&gt;   &lt;% unless firsts.include?(report.host) %&gt;     &lt;% firsts &lt;&lt; report.host %&gt;     &lt;tr&gt;       &lt;% unless params[:host_id] -%&gt;         &lt;td&gt;&lt;%= link_to h(report.host), host_reports_path(report.host) %&gt;&lt;/td&gt;       &lt;% end -%&gt;       &lt;td&gt;&lt;%= reported_at_column(report) %&gt;&lt;/td&gt;       &lt;td&gt;&lt;%= report_event_column(report.applied, "notice") %&gt;&lt;/td&gt;       &lt;td&gt;&lt;%= report_event_column(report.restarted, "notice") %&gt;&lt;/td&gt;       &lt;td&gt;&lt;%= report_event_column(report.failed, "important") %&gt;&lt;/td&gt;       &lt;td&gt;&lt;%= report_event_column(report.failed_restarts, "warning") %&gt;&lt;/td&gt;       &lt;td&gt;&lt;%= report_event_column(report.skipped, "notice") %&gt;&lt;/td&gt;       &lt;td align="right"&gt;         &lt;%= display_link_if_authorized "Destroy", hash_for_report_path(:id =&gt; report.id, :auth_a ction =&gt; :destroy), :confirm =&gt; "Delete report for #{report.host.name}?", :method =&gt; :delete %&gt;       &lt;/td&gt;     &lt;/tr&gt;   &lt;% end %&gt; &lt;% end %&gt; &lt;/table&gt; &lt;%= will_paginate @reports %&gt;</pre>	