

Installer - Feature #16720

Create DH parameter and setup foremans vhost config with it

09/28/2016 09:19 AM - Christian Schmitt

Status: Rejected	
Priority: Normal	
Assignee:	
Category: Foreman modules	
Target version:	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases: 1.13.0
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description	
<p>Since you are aware of this issue: [[https://tickets.puppetlabs.com/browse/SERVER-17]], I think foreman installer should trigger the creation of a custom dhparam and setup the foreman vhost config with it.</p> <p>This would create a better "out of the box" experience. Now it is like: install a current version of a Linux distribution, install foreman, attach some hosts to puppet... hmmm damn no reports from puppet... browse the log files ... find the java dh parameter exception ... do some googling... find the thread mentionen above... try to fix it</p> <p>You could use openssl for creation, e.g.: <code>openssl dhparam -out dhparam.pem 2048 -dsaparam (dsaparam makes it much faster)</code></p>	

History

#1 - 10/07/2017 02:22 PM - Anonymous

- Category changed from *foreman-installer script* to *Foreman modules*
- Status changed from *New* to *Rejected*
- Difficulty deleted (*easy*)

the underlying problem is fixed with Puppetserver 5.x

#2 - 10/11/2017 03:59 AM - Christian Schmitt

Could you provide some more details? Where are these infos from?
IMHO it's more a problem with Java in relation to the apache configuration of the foreman vhost.
What would it have to do with Puppetserver? Is Puppetserver not implemented in Java anymore?

#3 - 10/11/2017 05:30 AM - Anonymous

I can only say it's working just fine out of the box with PS5, I guess they switched to deploy the Bouncycastle security provider or something similar in the Puppetserver JAR.