Foreman - Support #17275

Deploy windows and userdata template

11/08/2016 11:31 AM - Sam Amara

Status: Resolved

Priority: Assignee:

Category: Unattended installations

Normal

Target version:

Triaged: Found in Releases:

Fixed in Releases:

Description

Hello,

I need to deploy a windows template with foreman.

For that purpose, I associated this userdata template with an windows operating system.

```
<%-
 powershell = '%SystemRoot%\System32\WindowsPowerShell\v1.0\powershell.exe -ExecutionPolicy Unres
tricted -NoLogo -NoProfile'
-응>
identity:
  Sysprep:
    guiRunOnce:
     commandList:
       - '<%= powershell %> -Command "invoke-webrequest -Uri <%= foreman_url("built") %>"'
    guiUnattended:
      autoLogon: true
      autoLogonCount: 1
     password:
       plainText: true
        value: 'testpass123'
     timeZone: 110
    identification:
      joinWorkgroup: 'MyGroup'
    licenseFilePrintData:
     autoMode: 'perSeat'
    userData:
      computerName: <%= @host.shortname %>
      fullName: 'IT'
      orgName: 'MyOrg'
     productId: 'D2N9P-3P6X9-2R39C-7RTCD-MDVJX'
nicSettingMap:
  - adapter:
      dnsDomain: <%= @host.domain %>
      dnsServerList:
       - <%= @host.subnet.dns_primary %>
globalIPSettings:
 dnsServerList:
    - <%= @host.subnet.dns_primary %>
 dnsSuffixList:
    - <%= @host.domain %>
options:
 changeSID: true
 deleteAccounts: false
```

After deploying a vm, a build property is still on "Pending installation" and to my knowledge none of this data is passed.

Somebody can help me please?

05/18/2024 1/2

History

#1 - 11/09/2016 03:21 AM - Dominic Cleal

- Status changed from New to Feedback

The host must make an HTTP request to http(s)://foreman.example.com/unattended/built at boot, e.g. via a script at startup. Consider adding it to your image.

Please prefer the foreman-users mailing list or IRC channel for support, there are many more people reading it.

#2 - 11/09/2016 03:46 AM - Sam Amara

That is what I tried to do with this powershell command in a user data template: '<%= powershell > -Command "invoke-webrequest -Uri <= foreman_url("built") %>"

When I launch manually this command after startup, it works but not with userdata template. Why?

Thanks for your help.

#3 - 11/09/2016 03:49 AM - Dominic Cleal

If it logs a request on Foreman then please provide the log, and I may be able to help. If it doesn't reach Foreman then I can't assist - somebody else may, but you're more likely to get a response on the mailing list.

#4 - 11/09/2016 04:23 AM - Sam Amara

Ok, thanks. I just create a new subject on the foreman users mailing list.

#5 - 03/10/2017 08:58 PM - Anonymous

- Status changed from Feedback to Resolved

#6 - 09/26/2017 04:40 AM - Pedro Jose Iglesias

Sam Amara wrote:

Ok, thanks. I just create a new subject on the foreman users mailing list.

Hi there,

For sure this will sounds like a stupid question but, would you mind to tell where can I find the steps or details to join the Mailing List. Thanks in advanced.

Regards.

#7 - 09/26/2017 12:46 PM - Marek Hulán

see https://theforeman.org/support.html

05/18/2024 2/2