

Foreman - Bug #17503

Host model load causes unnecessary loads on instantiation

11/28/2016 10:49 AM - Tomer Brisker

Status:	Closed	
Priority:	Normal	
Assignee:	Tomer Brisker	
Category:	Host creation	
Target version:	1.15.0	
Difficulty:		Fixed in Releases:
Triaged:		Found in Releases: 1.13.0
Bugzilla link:		Red Hat JIRA:
Pull request:	https://github.com/foreman/foreman/pull/4063	
Description		
The fix for #12634 introduced a PXELoaderSuggestion mechanism that is executed as an `after_initialize` hook. This causes any Host object instantiation to execute this suggestion mechanism, which may lead to up to 3 extra queries per host. However, this is only needed for the host creation form to populate the PXELoader field when choosing OS.		
Related issues:		
Related to Foreman - Feature #12634: New HW Model flag pxe_loader in UI/API		Closed 11/30/2015

Associated revisions

Revision 497c022b - 12/07/2016 02:26 AM - Tomer Brisker

Fixes #17503 - Only trigger PXELoader suggestion when needed

Previously every host instantiation triggered a PXELoader suggestion, which led to up to 3 extra queries per host loaded. This changes so that the suggestion is only applied when a host changes it's OS.

History

#1 - 11/28/2016 11:34 AM - The Foreman Bot

- Status changed from New to Ready For Testing
- Assignee set to Tomer Brisker
- Pull request <https://github.com/foreman/foreman/pull/4063> added

#2 - 11/29/2016 04:41 AM - Tomer Brisker

- Related to Feature #12634: New HW Model flag pxe_loader in UI/API added

#3 - 11/29/2016 10:05 AM - Daniel Lobato Garcia

- Target version set to 1.4.3

#4 - 12/07/2016 04:01 AM - Anonymous

- Status changed from Ready For Testing to Closed
- % Done changed from 0 to 100

Applied in changeset [497c022bf4f77819f1a9f781a762f212d82aad30](#).

#5 - 12/07/2016 04:58 AM - Dominic Cleal

- translation missing: en.field_release set to 209