

Smart Proxy - Refactor #1769

Refactor SETTINGS variables

07/19/2012 04:00 AM - Benjamin Papillon

<div>Status: Rejected</div> <div>Priority: Normal</div> <div>Assignee:</div> <div>Category:</div> <div>Target version:</div> <div>Difficulty:</div> <div>Triaged:</div> <div>Bugzilla link:</div> <div>Pull request:</div>	<div>Fixed in Releases:</div> <div>Found in Releases:</div> <div>Red Hat JIRA:</div>
<div>Description</div> <div>puppet proxy use puppet_conf variables</div> <div>puppetca proxy use puppetdir and ssl_dir variables</div> <div>It should be possible to rationalize these, for example :</div> <div>SETTINGS.puppetdir    "/etc/puppet"</div> <div>SETTINGS.puppetconf    puppetdir + "/puppet.conf"</div> <div>SETTINGS.puppetautosign    puppetdir + "/autosign.conf"</div> <div>SETTINGS.ssldir    "/var/lib/puppet/ssl"</div> <div>Better is to read ssldir from puppet.conf, dunno how hard is that.</div>	

History

#1 - 05/11/2016 10:58 AM - Anonymous

- Description updated
- Status changed from New to Rejected

Don't think this is relevant any longer, all puppet-related settings are contained within puppet plugin and/or related providers configuration files.