

Foreman - Feature #1799

Respect HTTP_X_FORWARDED_FOR for configured list of ip addresses.

08/01/2012 08:04 AM - Steve Traylen

Status:	Closed	Fixed in Releases: Found in Releases: Red Hat JIRA:
Priority:	Normal	
Assignee:	Hannes Schaller	
Category:	Unattended installations	
Target version:	1.1	
Difficulty:		
Triaged:		
Bugzilla link:		
Pull request:		
Description		
<p>Hi</p> <p>app/controllers/unattended_controller.rb</p> <p>contains:</p> <pre>elsif (ip = request.env['REMOTE_ADDR']) =~ /127.0.0/ ip = request.env["HTTP_X_FORWARDED_FOR"] unless request.env["HTTP_X_FORWARDED_FOR"].nil? end</pre> <p>i.e if connecting from localhost then respect the HTTP_X_FORWARDED_FOR for requests for e.g. http://judy.cern.ch/unattended/built</p> <p>Having set up a remote http load balancer in front of two foreman hosts this 127.0.0 needs to be configured to whatever that remote host is. After editing unattended_controller.rb to contain my balancers ip address the unattended scripts work as expected.</p>		
Related issues:		
Related to Foreman - Bug #21628: Using the setting "Update IP from built requ...		New 11/10/2017

Associated revisions

Revision 50e78f00 - 08/08/2012 07:01 AM - Hannes Schaller

fixes #1799 moved REMOTE_ADDR verification to settings

History

#1 - 08/01/2012 08:11 AM - Ohad Levy

what would you like we change? make it as a setting? or always respect the forwarded ip header?

#2 - 08/07/2012 06:42 AM - Ohad Levy

- Target version set to 1.1

#3 - 08/07/2012 06:42 AM - Ohad Levy

- Assignee changed from Ohad Levy to Hannes Schaller

fix at <https://github.com/theforeman/foreman/pull/126>

#4 - 08/08/2012 08:28 AM - Hannes Schaller

- Status changed from New to Closed

- % Done changed from 0 to 100

Applied in changeset [50e78f00209b13865702990f10430e7feed22b56](#).

#5 - 11/10/2017 11:41 AM - Ivan Necas

- Related to Bug #21628: Using the setting "Update IP from built request" when building host through proxy, the IP will be updated with the proxy instead of the host IP added