

Smart Proxy - Refactor #18398

Use consistent naming of parameters in the DNS modules

02/04/2017 11:58 AM - Ewoud Kohl van Wijngaarden

Status: Ready For Testing	
Priority: Normal	
Assignee: Ewoud Kohl van Wijngaarden	
Category: DNS	
Target version:	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request: https://github.com/theforeman/smart-proxy/pull/507	
Description	
<p>This comes from https://github.com/theforeman/smart-proxy/pull/490. Currently the API uses parameter names like fqdn which are ambiguous, in particular in the context of a CNAME where both the name and content are FQDNs.</p> <p>To avoid confusion I'm proposing to use the following naming scheme:</p> <ul style="list-style-type: none">• fqdn is what is defined in the API and should only be in dns_api.rb• value is what is defined in the API and should only be in dns_api.rb• name is the DNS name you query for• content is the result your DNS server should return	
Related issues:	
Related to Smart Proxy - Refactor #17880: DNS CNAME parameters methods are sw...	Rejected 12/29/2016

History

#1 - 02/04/2017 11:59 AM - The Foreman Bot

- Status changed from New to Ready For Testing

- Pull request <https://github.com/theforeman/smart-proxy/pull/507> added

#2 - 05/20/2017 10:40 AM - Anonymous

- Related to Refactor #17880: DNS CNAME parameters methods are swapped added