

Smart Proxy - Bug #1915

Proxy with puppet3 causes global load errors

10/24/2012 09:21 AM - Greg Sutcliffe

Status: Closed	
Priority: Normal	
Assignee: Dominic Cleal	
Category: Puppet	
Target version: 1.1	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description	
If you curl the environment api call more than once, you get this:	
root@installer:~# curl http://localhost:8445/puppet/environments ["development","production"]	
root@installer:~# curl http://localhost:8445/puppet/environments Failed to list puppet environments: Attempting to initialize global default settings more than once!	
This seems to be a puppet3 thing, there is some data on puppet-dev that might help...	

Associated revisions

Revision ff16a263 - 11/22/2012 10:17 AM - Dominic Cleal

fixes #1915 - initialise Puppet in master context

Explicitly specify the run_mode as being 'master' to ensure the config is parsed in a puppetmaster context.

Revision a07f4bd0 - 11/22/2012 10:37 AM - Dominic Cleal

fixes #1915 - load environments from Puppet 3

Two changes to support loading environment settings from Puppet 3:

- explicitly specify the run_mode as being 'master' to ensure the config is parsed in a puppetmaster context
- call private method to fully clear the state in Puppet::Settings allowing for a full reparsing of the config to pick up changes in environments (Puppet bug #17783)

History

#1 - 11/06/2012 10:33 AM - Sam Kottler

I can pull this in as part of the puppet 3 work I'm doing. Can you provide a link to the puppet-dev email?

#2 - 11/07/2012 03:37 AM - Daniel Gagnon

Hi,

I am in the process of getting Foreman to work with puppet3 on Debian squeeze.

For this particular problem, here is what I did:

```
/usr/share/foreman-proxy/lib/proxy/puppet/environment.rb => replace "Puppet.parse_config" with:  
if $isLoaded == nil  
  puts "loading"  
  Puppet.settings.initialize_global_settings(['--config=/etc/puppet/puppet.conf'])  
  $isLoaded = true  
else  
  puts "already loaded"  
end
```

also add the snippet inside the load method of `/usr/share/foreman/lib/foreman/default_settings/loader.rb`

Last thing is to remove `Puppet.parse`.

Hope it works for you.

#3 - 11/07/2012 08:51 AM - Sam Kottler

- Assignee changed from Greg Sutcliffe to Sam Kottler

#4 - 11/07/2012 02:30 PM - eric sorensen

This is the puppet-dev thread: <https://groups.google.com/d/topic/puppet-dev/Yk0WC1JZCg8/discussion>

Chris Price's post there is valuable because he suggests that the entry point `Puppet.initialize_settings` is the simplest / most accessible method to call, but it implies a `:user` run-mode. If that's not what you want (because that would skip settings in the `[master]` section of the config file), my suggestion from tracing through this yesterday would be to do :

```
Puppet.settings.initialize_global_settings(['--config=/etc/puppet/puppet.conf', '--run_mode=master'])
```

The puppet platform devs are planning to get this cleaned up and documented for 3.1; we are sorry for the churn on it but several band-aid attempts caused bad follow-on effects so it's getting a properly engineered solution.

#5 - 11/16/2012 03:51 PM - Carlos Aguado

After applying the change on `Puppet.parse_config` to

```
Puppet.settings.initialize_global_settings(Puppet[:config]) unless Puppet.settings.global_defaults_initialized?
```

had to comment out
`#Puppet.clear`

#6 - 11/21/2012 03:06 PM - Dominic Cleal

- Category set to *Puppet*
- Status changed from *New* to *Assigned*
- Assignee changed from *Sam Kottler* to *Dominic Cleal*

Two pulls to address this, the main one being for the smart proxy, but related was one in foreman itself:

- <https://github.com/theforeman/smart-proxy/pull/42>
- <https://github.com/theforeman/foreman/pull/258>

Thanks for the suggestion Eric, that helped solve the problems seen initialising some basic settings such as `confdir` and `vardir` when the `run_mode` wasn't specified. I've worked around [#17492](#) with `--run_mode` and also fixed the original bug report here with a hack until a public interface is added in Puppet 3.1 to enable full reparsing of the config ([#17783](#)).

#7 - 11/22/2012 10:18 AM - Ohad Levy

- Target version set to *1.1*

#8 - 11/22/2012 10:22 AM - Dominic Cleal

- Status changed from *Assigned* to *Closed*
- % Done changed from *0* to *100*

Applied in changeset commit:"ff16a263433c5f3202b81663ba9a6745dd11a047".