

Foreman - Bug #1920

Template URLs should not be based on the browser address bar

10/29/2012 10:23 AM - Greg Sutcliffe

Status: Closed	
Priority: Normal	
Assignee: Greg Sutcliffe	
Category: Templates	
Target version: 1.1	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description	
Templates are generated using <code>url_for()</code> which causes the templates to get the base url of the foreman server from the user's web browser address. This is incorrect if you're installing Foreman locally and accessing http://localhost:3000/	
We should instead use the <code>Settings[:foreman_url]</code> value to construct the URLs. Patch incoming.	

Associated revisions

Revision f343e91a - 10/31/2012 05:35 AM - Greg Sutcliffe

Fixes #1920 - Template URLs should not be based on the browser address bar

Revision 9f6de1e7 - 11/01/2012 07:45 AM - Greg Sutcliffe

Refs #1920 : Fix failing tests for `Setting[:foreman_url]` Ensure plain 'http' protocol is used in templates Add a test to ensure http is used when https is in `@request`

History

#1 - 10/31/2012 06:41 AM - Anonymous

- Status changed from New to Closed

- % Done changed from 0 to 100

Applied in changeset [f343e91a2b65c1cf94d057359dd100f3a10b0cc7](https://gitlab.com/foreman/foreman/-/commit/f343e91a2b65c1cf94d057359dd100f3a10b0cc7).