

Foreman - Feature #1969

Override hostname of puppetmaster instead of using proxy hostname

11/22/2012 07:29 AM - Dominic Cleal

Status: New	
Priority: Normal	
Assignee:	
Category: Smart Proxy	
Target version:	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description	
<p>Foreman currently configures systems with a puppetmaster hostname of the smart proxy that is configured as the puppetmaster, but the hostname is Foreman's perspective of the proxy's hostname.</p> <p>For complex network environments (perhaps NATed or with access to the proxy tunnelled) then the hostname that Foreman sees isn't the same as the one the client systems should be using for the puppetmaster. It should be possible to override the puppetmaster hostname provided to systems somewhere.</p> <p>Possibly:</p> <ul style="list-style-type: none">• a parameter on the host or hostgroup that overrides the name• a config variable on the proxy itself that's passed through• an attribute on the smart proxy object	
Related issues:	
Related to Foreman - Feature #1970: Override the foreman_url hostname	New 11/22/2012

History

#1 - 12/04/2012 05:49 PM - Markus Nussdorfer

Have the same issue here.

puppet_server is set in settings.yaml and also shows the same value in the settings page.

But in the yaml output it gives me the proxy url for puppetmaster and puppet_ca