

## Foreman - Feature #21204

### Helper function to read settings and global default entry

10/05/2017 03:31 AM - Lukas Zapletal

<b>Status:</b>	Closed	
<b>Priority:</b>	Normal	
<b>Assignee:</b>	Lukas Zapletal	
<b>Category:</b>	Templates	
<b>Target version:</b>	1.18.0	
<b>Difficulty:</b>		<b>Fixed in Releases:</b>
<b>Triaged:</b>		<b>Found in Releases:</b>
<b>Bugzilla link:</b>		<b>Red Hat JIRA:</b>
<b>Pull request:</b>	<a href="https://github.com/theforeman/foreman/pull/4891">https://github.com/theforeman/foreman/pull/4891</a> , <a href="https://github.com/theforeman/community-templates/pull/430">https://github.com/theforeman/community-templates/pull/430</a> , <a href="https://github.com/theforeman/foreman/pull/5512">https://github.com/theforeman/foreman/pull/5512</a> , <a href="https://github.com/theforeman/community-templates/pull/509">https://github.com/theforeman/community-templates/pull/509</a>	
<b>Description</b> <p>Locked templates made very difficult to change to discovery in global default templates, user needs to unlock 2+2+2 (PXELinux, Grub, Grub2 template + discovery snippet) and make necessary changes just to change the default menu entry. This can be done via global setting.</p> <p>Edit: After some discussion, it will be required to have explicit list of global settings which can be accessed by the helper. Also templates can be also modified to use host/hostgroup parameter when present to override the default behavior.</p>		
<b>Related issues:</b> <p>Related to Foreman - Bug #24849: Use local instead of local_chain_hd0 default... <b>Closed</b></p>		

#### Associated revisions

##### Revision bdcdb09c - 02/23/2018 06:51 AM - Lukas Zapletal

Fixes #21204 - introduced global\_setting helper function (#4891)

##### Revision 0faf3900 - 03/16/2018 07:40 PM - Lukas Zapletal

Refs #21204 - default PXE entry from settings

##### Revision 9fa46aac - 05/02/2018 01:56 PM - Michael Moll

Refs #21204 - correct duplicate key in settings fixture

##### Revision db2f8275 - 10/05/2018 09:06 AM - Lukas Zapletal

Refs #21204 - use local as the default for grubs (#509)

#### History

##### #1 - 10/05/2017 04:10 AM - The Foreman Bot

- Status changed from New to Ready For Testing
- Assignee set to Lukas Zapletal
- Pull request <https://github.com/theforeman/community-templates/pull/430> added

##### #2 - 10/05/2017 04:10 AM - The Foreman Bot

- Pull request <https://github.com/theforeman/foreman/pull/4891> added
- Pull request deleted (<https://github.com/theforeman/community-templates/pull/430>)

##### #3 - 10/06/2017 09:22 AM - The Foreman Bot

- Pull request <https://github.com/theforeman/community-templates/pull/430> added

**#4 - 10/09/2017 09:56 AM - Lukas Zapletal**

- Description updated

Added some notes.

**#5 - 02/23/2018 06:51 AM - Marek Hulán**

- translation missing: en.field\_release set to 330

**#6 - 02/23/2018 07:01 AM - Lukas Zapletal**

- Status changed from Ready For Testing to Closed

- % Done changed from 0 to 100

Applied in changeset [bdcdb09ca3a39dc7cd117cdbf177491d1f45bf1d](#).

**#7 - 04/30/2018 01:01 PM - The Foreman Bot**

- Pull request <https://github.com/theforeman/foreman/pull/5512> added

**#8 - 09/10/2018 07:06 AM - Lukas Zapletal**

- Related to Bug #24849: Use local instead of local\_chain\_hd0 default setting for local templates added

**#9 - 09/10/2018 07:14 AM - The Foreman Bot**

- Pull request <https://github.com/theforeman/community-templates/pull/509> added