

Foreman - Bug #21426

PXELoader not inherited from the parent host group

10/23/2017 01:42 PM - Daniel Lobato Garcia

Status: Resolved	
Priority: Normal	
Assignee:	
Category: Host groups	
Target version: 1.15.5	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link: 1503834	Red Hat JIRA:
Pull request:	
Description Cloned from https://bugzilla.redhat.com/show_bug.cgi?id=1503834	
Description of problem: the pxeloder option is not properly inherited from the parent host group and stays at 'no value'.	
Version-Release number of selected component (if applicable): 6.3.0-20	
Steps to Reproduce: 1. create a host group, choose some OS and some PXEloader 2. create a nested host group and check its pxeloder option	
Actual results: Inherit (no value)	
Expected results: Inherit (the parent hg pxeloder value)	

History

#1 - 10/27/2017 07:42 AM - Lukas Zapletal

- Subject changed from PXELoader not inherited from the parent host group to PXELoader not inherited from the parent host group
- Status changed from New to Resolved
- translation missing: en.field_release set to 311

Daniel, this was fixed in 1.16 but did not make it into 1.15: Fixes [#18381](#) - PXE loader show inherited value in host/hostgroup

```
[lzap@box foreman]$ g tag --contains b8b00a962d4f1a8ba21877896254845599474946
1.16.0-RC1
1.16.0-RC2
```