

## Foreman - Feature #217

**Before deleting a Hostgroup, warn that the hostgroup is in use.**

04/16/2010 08:21 PM - Bash Shell

<b>Status:</b> Closed	
<b>Priority:</b> Normal	
<b>Assignee:</b>	
<b>Category:</b> Web Interface	
<b>Target version:</b> 0.1-5	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b>	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	
<b>Description</b>	
Users will go through some effort when they create a Hostgroup, and assign classes and group parameters.	
Then they add many hosts to this Hostgroup.	
If they delete the Hostgroup (by mistake or mis-communication), this effort may be wasted.	
It would be great if Foreman did not allow deletion of Hostgroups that are in use.	
This can be done by using "before_destroy Ensure_not_used_by.new(:hosts, :puppetclasses)"	
But ideally, the delete link should show a summary of what Hosts (and Group Parameters) will be affected after you click delete and confirm the deletion.	

### Associated revisions

#### Revision 17a015c2 - 04/22/2010 04:14 AM - Ohad Levy

fixes #217 - Before deleting a Hostgroup, warn that the hostgroup is in use.

### History

#### #1 - 04/17/2010 01:52 PM - Ohad Levy

- Category set to Web Interface

- Target version set to 0.1-5

Would you like to start with the simple solution? (ensure that its not used)

after [#200](#) is done, you could easily change the pop up text when pressing the delete link.

#### #2 - 04/27/2010 07:11 AM - Ohad Levy

- Status changed from New to Ready For Testing

- % Done changed from 0 to 100

Applied in changeset [17a015c200d0ffb2505ea125cfd99da3b7f2050](#).

#### #3 - 04/27/2010 07:16 AM - Ohad Levy

- Status changed from Ready For Testing to Closed