

Foreman - Bug #22556

Host search with parent_hostgroup returns all hosts when there are no matches

02/12/2018 02:49 PM - J. A.

Status: Closed	
Priority: Normal	
Assignee: Tomer Brisker	
Category:	
Target version: 1.18.0	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request: https://github.com/theforeman/foreman/pull/5249	
Description	
When searching for parent_hostgroup = "blablabla" where there is no hostgroup named "blablabla", the result includes all hosts. Performing the same search with other criteria like "name" or "comment" instead, the results includes no hosts when there are no matches. This is not necessarily a big deal for GUI searches, but for me it's problematic for API searches.	

Associated revisions

Revision 6beb3d8b - 02/13/2018 05:14 PM - Tomer Brisker

Fixes #22556 - Correct host search for parent hostgroup

Currently, searching on a non-existent parent fails due to `hostgroup.subtree_ids` throwing a NoMethodError when no matching hostgroup is found. This is rescued by scoped search, causing the search to run with no conditions instead.

(see

https://github.com/wvanbergen/scoped_search/blob/v4.1.2/lib/scoped_search/query_builder.rb#L405 for the scoped_search part)

History

#1 - 02/12/2018 03:23 PM - The Foreman Bot

- Status changed from New to Ready For Testing

- Assignee set to Tomer Brisker

- Pull request <https://github.com/theforeman/foreman/pull/5249> added

#2 - 02/13/2018 05:14 PM - Lukas Zapletal

- translation missing: en.field_release set to 330

#3 - 02/13/2018 06:01 PM - Anonymous

- Status changed from Ready For Testing to Closed

- % Done changed from 0 to 100

Applied in changeset [6beb3d8b15652e5a8dae3640806a1dbfca8b046](#).