

Installer - Feature #22570

Enable syslog for candlepin

02/13/2018 10:00 AM - Lukas Zapletal

Status: New	
Priority: Normal	
Assignee:	
Category: Foreman modules	
Target version:	
Difficulty:	Fixed in Releases:
Triaged: Yes	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description	
<p>By default candlepin uses rolling file appender, we want it to log into syslog which is currently supported upstream. Use local4 facility for all logs. By default candlepin does put correlation id (csid) on each line, the logging line should look like:</p> <pre><pattern>[%X{requestType}=%X{requestUuid}, org=%X{org}, csid=%X{csid}] %-5p %c - %m%n</pattern></pre> <p>More details how to configure syslog for candlepin: http://www.candlepinproject.org/docs/candlepin/logging.html#logging-to-syslog</p> <p>Also configure syslog to file all local4 logs into /var/log/candlepin/candlepin.log so users find it on the old path for easy transition. In the first phase, candlepin will only log in plaintext. Although it is possible to change the pattern to log in JSON format, installer will not support that for now.</p>	
Related issues:	
Related to Foreman - Tracker #22569: Unified and structured logging	Assigned

History

#1 - 02/13/2018 10:00 AM - Lukas Zapletal

- Related to Tracker #22569: Unified and structured logging added

#2 - 01/22/2019 03:49 PM - Lukas Zapletal

- Status changed from New to Assigned

Pattern proposal:

```
<pattern>@cee:{"message":"%m","foreman":{"request":"%X{csid}","org_id":"%X{org}"}, "candlepin":{"thread":"%thread","request_type":"%X{requestUuid}","request_uuid":"%X{requestUuid}"}}n</pattern>
```

#3 - 05/14/2020 01:47 PM - Zach Huntington-Meath

- Status changed from Assigned to New

- Triaged changed from No to Yes