

## Foreman - Bug #22765

### hammer organization add-location constructs invalid payload for PUT endpoint

03/05/2018 12:15 PM - roman plevka

<b>Status:</b> New	
<b>Priority:</b> Normal	
<b>Assignee:</b>	
<b>Category:</b> Organizations and Locations	
<b>Target version:</b>	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b> No	<b>Found in Releases:</b> Nightly
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	
<b>Description</b>	
<pre># hammer -d -u admin -p changeme organization add-location --location-id 2 --id 1 ... [ INFO 2018-03-05T07:14:14 API] PUT /katello/api/organizations/1 [DEBUG 2018-03-05T07:14:14 API] Params: {   "location_id" =&gt; 2,   "organization" =&gt; {     "location_ids" =&gt; [       [0] "2"     ]   } } [DEBUG 2018-03-05T07:14:14 API] Headers: {} [DEBUG 2018-03-05T07:14:14 API] Using authenticator: HammerCLIForeman::Api::InteractiveBasicAuth [ERROR 2018-03-05T07:14:14 API] 404 Not Found [DEBUG 2018-03-05T07:14:14 API] {   "error" =&gt; {     "message" =&gt; "Resource organization not found by id '1'"   } }</pre>	
there shouldn't be any "location_id" parameter put outside of the "organization" hash. Excluding this parameter from the payload makes the PUT request successful	

## History

### #1 - 03/05/2018 01:14 PM - roman plevka

version: katello-nightly (provisioned on 2018-03-04)

### #2 - 04/02/2019 05:12 PM - Oleh Fedorenko

Is it still reproducible (in Nightly)? I tried it now and it still builds the same payload, but works.

```
# hammer organization add-location --location-id 5 --id 4
...
[ INFO 2019-04-02T17:01:52 API] PUT /katello/api/organizations/4
[DEBUG 2019-04-02T17:01:52 API] Params: {
  "location_id" => 5,
  "organization" => {
    "location_ids" => [
      [0] "5"
    ]
  }
}
...
The location has been associated.
```