

Foreman - Bug #22882

Error generating gettext MO files when line ending is inconsistent

03/13/2018 03:48 PM - Ondřej Pražák

Status:	Closed	
Priority:	Normal	
Assignee:	Ondřej Pražák	
Category:		
Target version:	1.17.0	
Difficulty:		Fixed in Releases:
Triaged:		Found in Releases:
Bugzilla link:		Red Hat JIRA:
Pull request:		

Description

When running 'make -C locale all-mo', I got:

```
make: Entering directory `/home/vagrant/foreman/locale'
mkdir -p ca/LC_MESSAGES
msgfmt -o ca/LC_MESSAGES/foreman.mo ca/foreman.po
mkdir -p de/LC_MESSAGES
msgfmt -o de/LC_MESSAGES/foreman.mo de/foreman.po
mkdir -p en/LC_MESSAGES
msgfmt -o en/LC_MESSAGES/foreman.mo en/foreman.po
mkdir -p en_GB/LC_MESSAGES
msgfmt -o en_GB/LC_MESSAGES/foreman.mo en_GB/foreman.po
mkdir -p es/LC_MESSAGES
msgfmt -o es/LC_MESSAGES/foreman.mo es/foreman.po
mkdir -p fr/LC_MESSAGES
msgfmt -o fr/LC_MESSAGES/foreman.mo fr/foreman.po
mkdir -p gl/LC_MESSAGES
msgfmt -o gl/LC_MESSAGES/foreman.mo gl/foreman.po
mkdir -p it/LC_MESSAGES
msgfmt -o it/LC_MESSAGES/foreman.mo it/foreman.po
mkdir -p ja/LC_MESSAGES
msgfmt -o ja/LC_MESSAGES/foreman.mo ja/foreman.po
mkdir -p ko/LC_MESSAGES
msgfmt -o ko/LC_MESSAGES/foreman.mo ko/foreman.po
mkdir -p pl/LC_MESSAGES
msgfmt -o pl/LC_MESSAGES/foreman.mo pl/foreman.po
mkdir -p pt_BR/LC_MESSAGES
msgfmt -o pt_BR/LC_MESSAGES/foreman.mo pt_BR/foreman.po
mkdir -p ru/LC_MESSAGES
msgfmt -o ru/LC_MESSAGES/foreman.mo ru/foreman.po
mkdir -p sv_SE/LC_MESSAGES
msgfmt -o sv_SE/LC_MESSAGES/foreman.mo sv_SE/foreman.po
mkdir -p zh_CN/LC_MESSAGES
msgfmt -o zh_CN/LC_MESSAGES/foreman.mo zh_CN/foreman.po
zh_CN/foreman.po:7017: 'msgid' and 'msgstr[0]' entries do not both end with '\n'
msgfmt: found 1 fatal error
make: *** [zh_CN/foreman.mo] Error 1
make: Leaving directory `/home/vagrant/foreman/locale'
```

caused by:

```
msgid "Select this host"
msgid_plural "Select all <b> %{total} </b> hosts"
msgstr[0] ""
"#####\n"
"#### <b> %{total} </b> ##\n"
```

fixed version:

```
msgid "Select this host"  
msgid_plural "Select all <b> %{total} </b> hosts"  
msgstr[0] ""  
"##### \n"  
"#### <b> %{total} </b>  "
```

History

#1 - 03/14/2018 06:56 AM - Ondřej Pražák

- *Status changed from New to Closed*

#2 - 03/22/2018 09:07 AM - Lukas Zapletal

FYI we have "make check" target which performs check of messages. We should use that when merging i18n.