

## Installer - Bug #23905

### Default ansible\_dir should be ~foreman-proxy

06/12/2018 01:35 PM - Daniel Lobato Garcia

<b>Status:</b>	Closed	
<b>Priority:</b>	Normal	
<b>Assignee:</b>	Daniel Lobato Garcia	
<b>Category:</b>	Foreman modules	
<b>Target version:</b>	1.18.0	
<b>Difficulty:</b>		<b>Fixed in Releases:</b> 1.18.0
<b>Triaged:</b>	No	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	1590362	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	<a href="https://github.com/foreman/foreman/pull/432">https://github.com/foreman/foreman/pull/432</a>	
<b>Description</b>		
Otherwise, ~foreman-proxy/.ansible.cfg settings are ignored when running Ansible jobs.		

#### Associated revisions

##### Revision 4acf2d6a - 06/16/2018 12:45 PM - Daniel Lobato Garcia

Fixes #23905 - Use /usr/share/foreman-proxy as ansible\_dir

Using /etc/ansible means that the ~foreman-proxy/.ansible.cfg file we had set up will be ignored. This means the callback is ignored and any other options we might set in /etc/foreman-proxy/ansible.cfg

#### History

##### #1 - 06/12/2018 01:35 PM - Daniel Lobato Garcia

- Project changed from Foreman to Installer

##### #2 - 06/12/2018 01:37 PM - Daniel Lobato Garcia

- Category set to Foreman modules

##### #3 - 06/12/2018 01:38 PM - Daniel Lobato Garcia

- Bugzilla link set to 1590362

##### #4 - 06/12/2018 01:44 PM - Ewoud Kohl van Wijngaarden

IMHO it should be configurable. Ideally we can change it to /etc/foreman-proxy/ansible in production for configs and /var/lib/foreman-proxy/ansible for state. Currently we do this via symlinks in RPMs but that's a bit ugly IMHO.

##### #5 - 06/12/2018 01:53 PM - The Foreman Bot

- Status changed from New to Ready For Testing

- Assignee set to Daniel Lobato Garcia

- Pull request <https://github.com/foreman/foreman/pull/432> added

##### #6 - 06/12/2018 02:06 PM - Daniel Lobato Garcia

It's configurable already, both in the installer or manually changing /etc/foreman-proxy/settings.d/ansible.yml. The issue is really just about the default value

##### #7 - 06/12/2018 05:44 PM - Marek Hulán

I think the suggested change is valid and already an improvement to current state. Even though config should not live in /usr, that's how we configure foreman-proxy user home and that is where ansible searches for its config. Opening a refactoring issue for later split would be good, but we'd need to handle upgrade path too. Sounds big for something we'll require for 1.18

##### #8 - 06/16/2018 01:01 PM - Anonymous

- Status changed from Ready For Testing to Closed
- % Done changed from 0 to 100

Applied in changeset [puppet-foreman\\_proxy/4acf2d6a073e43c1501bf78f986fee6dea917c68](#).

**#9 - 07/12/2018 02:06 PM - Ewoud Kohl van Wijngaarden**

- Target version set to 1.18.0
- Triaged set to No
- Fixed in Releases 1.18.0 added