

Installer - Bug #23919

installer breaks if TMPDIR and/or TMP is set.

06/13/2018 01:17 PM - Han Boetes

Status: New	
Priority: Normal	
Assignee:	
Category:	
Target version:	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description	
<p>With help from tbrisker@irc.freenode.net I found out the installer fails if TMP and/or TMPDIR is set to a directory not writable by user other than root.</p> <pre>1. foreman-rake db:migrate db:seed mktemp: failed to create file via template '/root/.local/tmp/tmp.XXXXXXXXXX': Permission denied /usr/bin/tfm-rake: line 6: \$TMP: ambiguous redirect /usr/bin/tfm-rake: line 8: \$TMP: ambiguous redirect /usr/bin/tfm-rake: line 8: \$TMP: ambiguous redirect bash: no job control in this shell</pre> <p>after unsetting TMP and TMPDIR and running the installer again, the installation finishes succesfully.</p>	

History

#1 - 06/13/2018 01:29 PM - Han Boetes

I'd also like to mention that the installer should have stopped when the db setup failed. It simply continued and made me search for something unrelated.

#2 - 06/13/2018 08:43 PM - Ewoud Kohl van Wijngaarden

I suspect this is actually an issue in foreman-rake which is a bash script. I suspect that it exits with code 0 so the installer continues.