

Installer - Bug #23919

installer breaks if TMPDIR and/or TMP is set.

06/13/2018 01:17 PM - Han Boetes

Status:	New	
Priority:	Normal	
Assignee:		
Category:		
Target version:		
Difficulty:		Fixed in Releases:
Triaged:		Found in Releases:
Bugzilla link:		Red Hat JIRA:
Pull request:		

Description

With help from tbrisker@irc.freenode.net I found out the installer fails if TMP and/or TMPDIR is set to a directory not writable by user other than root.

```
1. foreman-rake db:migrate db:seed
mktemp: failed to create file via template '/root/.local/tmp/tmp.XXXXXXXXXX': Permission denied
/usr/bin/tfm-rake: line 6: $TMP: ambiguous redirect
/usr/bin/tfm-rake: line 8: $TMP: ambiguous redirect
/usr/bin/tfm-rake: line 8: $TMP: ambiguous redirect
bash: no job control in this shell
```

after unsetting TMP and TMPDIR and running the installer again, the installation finishes succesfully.

History

#1 - 06/13/2018 01:29 PM - Han Boetes

I'd also like to mention that the installer should have stopped when the db setup failed. It simply continued and made me search for something unrelated.

#2 - 06/13/2018 08:43 PM - Ewoud Kohl van Wijngaarden

I suspect this is actually an issue in foreman-rake which is a bash script. I suspect that it exits with code 0 so the installer continues.