

Foreman - Refactor #23930

Foreman prefers PXEGrub2 UEFI loader for generic host

06/14/2018 06:37 AM - Lukas Zapletal

Status: Closed	
Priority: Normal	
Assignee: Lukas Zapletal	
Category: Host creation	
Target version: 1.18.0	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases: 1.18.0-RC1
Bugzilla link:	Red Hat JIRA:
Pull request: https://github.com/theforeman/foreman/pull/5691 , https://github.com/theforeman/foreman/pull/5702	
Description	
When new bare-metal host is created and all PXE template kinds are associated and set for selected OS, Foreman sets PXE loader in this order:	
<ul style="list-style-type: none">• PXEGrub2 UEFI• PXELinux BIOS• PXEGrub UEFI	
We should still prefer BIOS as the primary options because this can end up with hosts not booting for users with BIOS-PXE workflow which is still the most used one.	

Associated revisions

Revision [b7fc06c4](#) - 06/18/2018 07:22 AM - Lukas Zapletal

Fixes #23930 - PXELinux loader is now preferred

History

#1 - 06/14/2018 09:58 AM - The Foreman Bot

- Status changed from New to Ready For Testing

- Pull request <https://github.com/theforeman/foreman/pull/5691> added

#2 - 06/14/2018 10:13 AM - Lukas Zapletal

- translation missing: en.field_release set to 330

#3 - 06/15/2018 05:27 PM - The Foreman Bot

- Pull request <https://github.com/theforeman/foreman/pull/5702> added

#4 - 06/18/2018 08:01 AM - Lukas Zapletal

- Status changed from Ready For Testing to Closed

- % Done changed from 0 to 100

Applied in changeset [b7fc06c4aadd247c522b757e01e5992749ad9b16](#).