

## Foreman - Bug #24217

### Support shell script cloud-init format for oVirt

07/10/2018 10:18 AM - Ivan Necas

<b>Status:</b>	Closed	
<b>Priority:</b>	Normal	
<b>Assignee:</b>	Ivan Necas	
<b>Category:</b>	Compute resources - oVirt	
<b>Target version:</b>		
<b>Difficulty:</b>		<b>Fixed in Releases:</b> 1.19.0
<b>Triaged:</b>	No	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	1481315	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	<a href="https://github.com/theforeman/foreman/pull/5806">https://github.com/theforeman/foreman/pull/5806</a>	
<b>Description</b>		
When the cloud-init script starts with `#!/usr/bin/bash`, the script is not sent as user-data to the oVirt.		
The shell script is a valid cloud-init format ( <a href="https://cloudinit.readthedocs.io/en/latest/topics/format.html">https://cloudinit.readthedocs.io/en/latest/topics/format.html</a> ) and even our default user-script is in the shell format.		
<b>Related issues:</b>		
Related to Foreman - Feature #20590: Full cloud-init support with ovirt provider		<b>Closed</b> 08/14/2017

#### Associated revisions

##### Revision 0385aedf - 07/13/2018 08:42 AM - Ivan Necas

Fixes #24217 - accept shell script for cloud-init in oVirt

Our default user\_data template uses shell format for cloud-init: we should be able to use it for oVirt as well, especially after #24217 has been fixed.

#### History

##### #1 - 07/10/2018 10:26 AM - Ivan Necas

- Related to Feature #20590: Full cloud-init support with ovirt provider added

##### #2 - 07/10/2018 10:30 AM - The Foreman Bot

- Status changed from Assigned to Ready For Testing

- Pull request <https://github.com/theforeman/foreman/pull/5806> added

##### #3 - 07/13/2018 09:01 AM - Ivan Necas

- Status changed from Ready For Testing to Closed

- % Done changed from 0 to 100

Applied in changeset [0385aedfb48dc32756d21e7143ae1ea57d31078c](#).

##### #4 - 08/29/2018 03:13 PM - Tomer Brisker

- Fixed in Releases 1.19.0 added