

Foreman - Bug #24217

Support shell script cloud-init format for oVirt

07/10/2018 10:18 AM - Ivan Necas

Status:	Closed	
Priority:	Normal	
Assignee:	Ivan Necas	
Category:	Compute resources - oVirt	
Target version:		
Difficulty:		Fixed in Releases: 1.19.0
Triaged:	No	Found in Releases:
Bugzilla link:	1481315	Red Hat JIRA:
Pull request:	https://github.com/foreman/foreman/pull/5806	
Description		
When the cloud-init script starts with `#!/usr/bin/bash`, the script is not sent as user-data to the oVirt.		
The shell script is a valid cloud-init format (https://cloudinit.readthedocs.io/en/latest/topics/format.html) and even our default user-script is in the shell format.		
Related issues:		
Related to Foreman - Feature #20590: Full cloud-init support with ovirt provider	Closed	08/14/2017

Associated revisions

Revision 0385aedf - 07/13/2018 08:42 AM - Ivan Necas

Fixes #24217 - accept shell script for cloud-init in oVirt

Our default user_data template uses shell format for cloud-init: we should be able to use it for oVirt as well, especially after #24217 has been fixed.

History

#1 - 07/10/2018 10:26 AM - Ivan Necas

- Related to Feature #20590: Full cloud-init support with ovirt provider added

#2 - 07/10/2018 10:30 AM - The Foreman Bot

- Status changed from Assigned to Ready For Testing

- Pull request <https://github.com/foreman/foreman/pull/5806> added

#3 - 07/13/2018 09:01 AM - Ivan Necas

- Status changed from Ready For Testing to Closed

- % Done changed from 0 to 100

Applied in changeset [0385aedfb48dc32756d21e7143ae1ea57d31078c](https://github.com/foreman/foreman/pull/5806).

#4 - 08/29/2018 03:13 PM - Tomer Brisker

- Fixed in Releases 1.19.0 added