

## Foreman - Bug #2562

### Hosts created with wrong listen address

05/26/2013 04:27 AM - Ryan Davies

<b>Status:</b> Closed	
<b>Priority:</b> Normal	
<b>Assignee:</b>	
<b>Category:</b> VM management	
<b>Target version:</b> 1.2.0	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b>	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	
<b>Description</b>	
Setting the listen address for new domains to 0 is breaking libvirt's API standard, <a href="http://libvirt.org/formatdomain.html#elementsGraphics">http://libvirt.org/formatdomain.html#elementsGraphics</a>	
Changed lib/foreman/model/libvirt.rb#console: vm.update_display(:password => password, :listen => '0') to vm.update_display(:password => password, :listen => '0.0.0.0')	
The websocket still works (and starts working for existing systems), and virt-manager starts working again (For newly defined machines)	
See pull request <a href="https://github.com/theforeman/foreman/pull/626">https://github.com/theforeman/foreman/pull/626</a>	

#### Associated revisions

##### Revision 710dfa86 - 05/30/2013 09:41 AM - Ryan Davies

fixes #2562 libvirt domain listen address, add libvirt\_default\_console\_address setting

##### Revision c8151d16 - 05/30/2013 12:51 PM - Ryan Davies

fixes #2562 libvirt domain listen address, add libvirt\_default\_console\_address setting (cherry picked from commit 710dfa86835e7b8b430cf59646a7888746c3b0bc)

#### History

##### #1 - 05/30/2013 09:41 AM - Dominic Cleal

- Status changed from New to Ready For Testing
- Priority changed from High to Normal

<https://github.com/theforeman/foreman/pull/626>

##### #2 - 05/30/2013 10:17 AM - Ryan Davies

- Status changed from Ready For Testing to Closed
- % Done changed from 0 to 100

Applied in changeset [710dfa86835e7b8b430cf59646a7888746c3b0bc](https://github.com/theforeman/foreman/pull/626).